



Tridion Docs 15.1 Content Manager Installation Guide

Tridion Docs Content Manager 15.1.1

June 2024

Legal notice

Copyright and trademark information relating to this product release.

Copyright © 2003–2024 RWS Holdings plc. All rights reserved.

This legal notice applies to RWS Holdings plc and its subsidiaries and affiliates. All intellectual property rights contained herein are the sole and exclusive rights of RWS. All references to RWS shall mean RWS Holdings plc and its subsidiaries and affiliates details of which can be obtained upon written request.

All rights reserved. Unless explicitly stated otherwise, all intellectual property rights including those in copyright in the content of this website and documentation are owned by or controlled for these purposes by RWS. Except as otherwise expressly permitted hereunder or in accordance with copyright legislation, the content of this site, and/or the documentation may not be copied, reproduced, republished, downloaded, posted, broadcast or transmitted in any way without the express written permission of RWS.

Tridion Docs is a registered trademark of RWS. All other trademarks are the property of their respective owners. The names of other companies and products mentioned herein may be the trademarks of their respective owners. Unless stated to the contrary, no association with any other company or product is intended or should be inferred.

This product may include open source or similar third-party software, details of which can be found by clicking the following link: "Acknowledgments " on page 2 .

Although RWS takes all reasonable measures to provide accurate and comprehensive information about the product, this information is provided as-is and all warranties, conditions or other terms concerning the documentation whether express or implied by statute, common law or otherwise (including those relating to satisfactory quality and fitness for purposes) are excluded to the extent permitted by law.

To the maximum extent permitted by law, RWS shall not be liable in contract, tort (including negligence or breach of statutory duty) or otherwise for any loss, injury, claim liability or damage of any kind or arising out of, or in connection with, the use or performance of the Software Documentation even if such losses and/or damages were foreseen, foreseeable or known, for: (a) loss of, damage to or corruption of data, (b) economic loss, (c) loss of actual or anticipated profits, (d) loss of business revenue, (e) loss of anticipated savings, (f) loss of business, (g) loss of opportunity, (h) loss of goodwill, or (i) any indirect, special, incidental or consequential loss or damage howsoever caused.

All Third Party Software is licensed "as is." RWS makes no warranties, express, implied, statutory or otherwise with respect to the Third Party Software, and expressly disclaims all implied warranties of non-infringement, merchantability and fitness for a particular purpose. **In no event will Licensor be liable for any damages, including loss of data, lost profits, cost of cover or other special, incidental, consequential, direct, actual, general or indirect damages arising from the use of the Third Party Software or accompanying materials, however caused and on any theory of liability. This limitation will apply even if Licensor has been advised of the possibility of such damage. The parties acknowledge that this is a reasonable allocation of risk.**

Information in this documentation, including any URL and other Internet website references, is subject to change without notice. Without limiting the rights under copyright, no part of this may be reproduced, stored in or introduced into a retrieval system, or transmitted in any

form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of RWS.

Contents

1	Welcome to the Tridion Docs 15.1 Content Manager Installation Guide	1
	Acknowledgments	2
	Customer support	29
2	Installing Content Manager	31
	Content Manager requirements	32
	Content Manager hardware requirements	32
	Content Manager software requirements	33
	Installer User Requirements	35
	Platform virtualization	36
	Firewalls and ports	36
	Content Manager pre-installation tasks	37
	Enabling https on the IIS website	37
	Defining the bindings in the target website	38
	Microsoft Windows Server	39
	Establishing a dedicated system user	40
	Changing the Local Group Policy	41
	Defining the location of the Oracle tnsnames.ora file	42
	Configuring HTTP Activation for WCF	42
	Configuring IIS web services	43
	Configuring IIS applicationHost.Config	44
	Prerequisites for Java	45
	Prerequisites for publishing engine	46
	Java Help	46
	HTML Help Workshop	46
	Antenna House XSL Formatter	46
	Content Manager pre-installation checklist	47
	Creating Content Manager databases	48
	Setting up the Content Manager database on Microsoft SQL Server	48
	Configuring Microsoft SQL Server	49
	Creating a Microsoft SQL Server database for Content Manager	49
	Importing data from the SQL dumpfile	50
	Removing the database user and schema	51
	Creating a new database user and schema	52
	Optionally minimize the database user's roles and permissions	53
	Setting up the Content Manager database for Oracle	55
	Configuring Oracle	56

Oracle database configuration requirements	56
Activating the Listener service for Oracle	56
Creating the Oracle database for the Content Manager Repository	57
Creating the designated ISOURCE database user	58
Importing the data with Oracle	59
Disabling optimizer dynamic sampling	60
Validating the Oracle database	60
Editing tnsnames.ora for an Oracle database	71
Analyzing the Oracle database	62
Creating databases for Content Manager security	62
Creating a database system administrator user for Oracle	64
Creating the Access Management database	64
Creating the Tridion Docs Identity Provider database	65
Creating the Backend for Frontend database	66
Creating the Metrics database	67
Installing the Content Manager server	69
Configuring database connection strings	69
Sample database connection strings	69
Editing tnsnames.ora for an Oracle database	71
Preparing the inputparameters.xml file	72
Mandatory input parameters in inputparameters.xml	73
Optional input parameters in inputparameters.xml	74
Executing the InstallTool	77
Identifying connection issues caused by reverse proxies	77
Installing desktop client tools	78
Uninstalling desktop client tools (upgrade only).	78
Installing the Authoring Bridge	78
Installing Publication Manager	79
Installing Condition Manager	79
Installing Content Importer	80
After the Content Manager installation	80
Creating a ServiceUser user	80
Reapplying custom Content Manager Add-ons	81
Synchronizing the Content Manager database with Metrics storage	81
Verifying Microsoft SQL System Administration role permissions	83
Running DBUpgradeTool for maintenance	83
Troubleshooting DBUpgradeTool	84

Installing ISHDeploy and ISHRemote	85
Checking translation services roles and privileges	86
Enabling Content Manager user interfaces and features	88
Enabling Draft Space	88
Enabling Review Space	88
Enabling Document History for Draft Space	89
Enabling Document History for Review Space	90
Setting the Collective Spaces URL for your accounts	91
Enabling services	91
Configure Security Token Service for authenticating WCF .SVC web services (deprecated)	92
Web Services requirements for Security Token Service	92
ISHSTS with Windows Authentication	94
Configure application server for Windows Authentication	95
Configuring the Content Manager SQL Server database for Windows Authentication	95
Verifying the installation	96
Verifying URLs	97
Verify read access to the database by viewing an inbox	97
Verify read and write access to the database by creating a folder	98
Creating an account and connecting to the Repository	98
Running a client tool	99
Testing publishing	99
Executing the full text search	100
Verifying customer specific components	100
Advanced topics for installation	100
InstallTool	100
InstallTool overview	101
The InstallTool package	101
Unimplemented features of the InstallTool	102
Firewalls and blocked ports	102
SMTP	103
Microsoft SQL Server ports	103
Oracle ports and protocols	105
HTTPS (SSL)	105
3 Troubleshooting Content Manager installation	107
Contacting customer support	108
Diagnosing Problems	108
Providing Information	108

Log Files	109
Using log files	109
Server Logs	109
Desktop client logs	112
Configuring logging for Content Manager .NET components	113
Event Log content	114
Using the Event Log	115
Troubleshooting the database installation	115
What to do if Oracle database import fails	116
What to do in case of "ORA-12638" error	116
User is restricted or does not have permissions	116
Login time restriction	116
User account restriction	117
User not granted requested logon type	118
The designated user is running the wrong (date) settings	118
Resolving certificate problems	119
Accepting a certificate using a web browser	119
Importing and accepting a certificate for a user	119
Importing and accepting a certificate for a computer	120
Troubleshooting the install tool	121
Troubleshooting the crawler service	121

1

Welcome to the Tridion Docs 15.1 Content Manager Installation Guide

This document presents the complete Content Manager installation procedure and information.

Acknowledgments

Tridion Docs products include open source or similar third-party software.

[@ant-design/cssinjs](#)

Component level cssinjs solution used in ant.design. It's a subset of Emotion with design token logic wrapper.

[@ant-design/icons](#)

The abstract trees of the Ant Design SVG icons.

[@ant-design/icons-svg](#)

The abstract node of the Ant Design SVG icons.

[@ant-design/react-slick](#)

Carousel component built with React. It is a react port of slick carousel

[@emotion/hash](#)

A MurmurHash2 implementation

[@emotion/is-prop-valid](#)

Check whether a prop is valid for HTML and SVG elements

[@emotion/unitless](#)

An object of css properties that don't accept values with units

[@ljharb/through](#)

Easy way to create a Stream that is both readable and writable.

[@monaco-editor/react](#)

Monaco Editor for React

[@popperjs/core](#)

Tooltip & Popover Positioning Engine

[@rc-component/context](#)

React way perf context selector

[@rc-component/mini-decimal](#)

A mini decimal calculator which only supports add, multi or compare operation for mini bundle size.

[@rc-component/mutate-observer](#)

MutateObserver for React.

[@rc-component/portal](#)

React 18 supported Portal Component.

[@rc-component/tour](#)

React 18 supported Tour Component.

[@types/hoist-non-react-statics](#)

This package contains type definitions for hoist-non-react-statics

[@types/prop-types](#)

This package contains type definitions for prop-types

[@types/react](#)

This package contains type definitions for react

[@types/scheduler](#)

This package contains type definitions for scheduler

[@types/stylis](#)

This package contains type definitions for stylis

[@types/use-sync-external-store](#)

This package contains type definitions for use-sync-external-store

[7zip](#)

Is a file archiver with a high compression ratio. 7-zip is delivered under the GNU LGPL License.

7zip SFX Modified Module

The SFX Modified Module is a plugin for creating self-extracting archives. It is compatible with three compression methods (LZMA, Deflate, PPMd) and provides an extended list of options. Reference website <http://7zsfx.info/>.

[Akka](#)

Akka is a toolkit and runtime for building highly concurrent, distributed, and fault tolerant event-driven applications on the JVM.

[Amazon Ion Java](#)

Amazon Ion Java is a Java streaming parser/serializer for Ion. It is the reference implementation of the Ion data notation for the Java Platform Standard Edition 8 and above.

[Amazon SQS Java Messaging Library](#)

This Amazon SQS Java Messaging Library holds the Java Message Service compatible classes, that are used for communicating with Amazon Simple Queue Service.

[Animal Sniffer Annotations](#)

Animal Sniffer Annotations provides Java 1.5+ annotations which allow marking methods which Animal Sniffer should ignore signature violations of.

[ansi-escapes](#)

ANSI escape codes for manipulating the terminal

[ansi-styles](#)

ANSI escape codes for styling strings in the terminal

[ANTLR](#)

ANTLR is a powerful parser generator that you can use to read, process, execute, or translate structured text or binary files.

Apache ActiveMQ

Apache ActiveMQ is the most popular and powerful open source messaging and Integration Patterns server.

Apache Ant

Apache Ant is a Java library and command-line tool whose mission is to drive processes described in build files as targets and extension points dependent upon each other. The main known usage of Ant is the build of Java applications. Ant supplies a number of built-in tasks allowing to compile, assemble, test and run Java applications. Ant can also be used effectively to build non Java applications, for instance C or C++ applications. More generally, Ant can be used to pilot any type of process which can be described in terms of targets and tasks.

Apache Commons BeanUtils

The Java language provides *Reflection* and *Introspection* APIs (see the `java.lang.reflect` and `java.beans` packages in the JDK Javadocs). However, these APIs can be quite complex to understand and utilize. The *BeanUtils* component provides easy-to-use wrappers around these capabilities.

Apache Commons Codec

Apache Commons Codec (TM) software provides implementations of common encoders and decoders such as Base64, Hex, Phonetic and URLs.

Apache Commons Collections

The Java Collections Framework was a major addition in JDK 1.2. It added many powerful data structures that accelerate development of most significant Java applications. Since that time it has become the recognized standard for collection handling in Java.

Apache Commons Compress

The Apache Commons Compress library defines an API for working with ar, cpio, Unix dump, tar, zip, gzip, XZ, Pack200, bzip2, 7z, arj, lzma, snappy, DEFLATE, lz4 and Z files.

Apache Commons Configuration

The Commons Configuration software library provides a generic configuration interface which enables a Java application to read configuration data from a variety of sources. Commons Configuration provides typed access to single, and multi-valued configuration parameters.

Apache Commons DBCP (Database Connection Pools)

Many Apache projects support interaction with a relational database. Creating a new connection for each user can be time consuming (often requiring multiple seconds of clock time), in order to perform a database transaction that might take milliseconds. Opening a connection per user can be unfeasible in a publicly-hosted Internet application where the number of simultaneous users can be very large. Accordingly, developers often wish to share a "pool" of open connections between all of the application's current users. The number of users actually performing a request at any given time is usually a very small percentage of the total number of active users, and during request processing is the only time that a database connection is required. The application itself logs into the DBMS, and handles any user account issues internally. There are several Database Connection Pools already available, both within Apache products and elsewhere. This Commons package provides an opportunity to coordinate the efforts required to create and maintain an efficient, feature-rich package under the ASF license.

[Apache Commons FileUpload](#)

The Commons **FileUpload** package makes it easy to add robust, high-performance, file upload capability to your servlets and web applications.

[Apache Commons HttpClient](#)

HttpClient was started in 2001 as a subproject of the Jakarta Commons, based on code developed by the Jakarta Slide project.

[Apache Commons IO](#)

Commons IO is a library of utilities to assist with developing IO functionality.

[Apache Commons JEXL \(Java Expression Language\)](#)

JEXL is a library intended to facilitate the implementation of dynamic and scripting features in applications and frameworks written in Java.

JEXL implements an Expression Language based on some extensions to the JSTL Expression Language supporting most of the constructs seen in shell-script or ECMAScript. Its goal is to expose scripting features usable by technical operatives or consultants working with enterprise platforms.

[Apache Commons Lang](#)

The standard Java libraries fail to provide enough methods for manipulation of its core classes. Apache Commons Lang provides these extra methods.

Lang provides a host of helper utilities for the java.lang API, notably String manipulation methods, basic numerical methods, object reflection, concurrency, creation and serialization and System properties. Additionally it contains basic enhancements to java.util.Date and a series of utilities dedicated to help with building methods, such as hashCode, toString and equals.

[Apache Commons Logging](#)

The Logging package is an ultra-thin bridge between different logging implementations. A library that uses the commons-logging API can be used with any logging implementation at runtime. Commons-logging comes with support for a number of popular logging implementations, and writing adapters for others is a reasonably simple task.

[Apache Commons Net](#)

Apache Commons Net™ library implements the client side of many basic Internet protocols. The purpose of the library is to provide fundamental protocol access, not higher-level abstractions.

[Apache Commons Pool](#)

Pool provides an Object-pooling API, with three major aspects:

1. A generic object pool interface that clients and implementers can use to provide easily interchangeable pooling implementations.
2. A toolkit for creating modular object pools.
3. Several general purpose pool implementations.

[Apache FOP](#)

Apache FOP (Formatting Objects Processor) is a print formatter driven by XSL formatting objects (XSL-FO) and an output independent formatter. It is a Java application that reads a formatting object (FO) tree and renders the resulting pages to a specified output. Output formats currently supported include PDF, PS, PCL, AFP, XML (area tree representation), Print, AWT and PNG, and to a lesser extent, RTF and TXT. The primary output target is PDF.

[Apache Geronimo](#)

Apache Geronimo is an open source server runtime that integrates the best open source projects to create Java/OSGi server runtimes that meet the needs of enterprise developers and system administrators.

[Apache HttpClient](#)

Although the `java.net` package provides basic functionality for accessing resources via HTTP, it doesn't provide the full flexibility or functionality needed by many applications. HttpClient seeks to fill this void by providing an efficient, up-to-date, and feature-rich package implementing the client side of the most recent HTTP standards and recommendations.

Designed for extension while providing robust support for the base HTTP protocol, HttpClient may be of interest to anyone building HTTP-aware client applications such as web browsers, web service clients, or systems that leverage or extend the HTTP protocol for distributed communication.

[Apache HttpComponents](#)

The Apache HttpComponents™ project is responsible for creating and maintaining a toolset of low level Java components focused on HTTP and associated protocols.

Within the HttpComponents project, [HttpCore](#) is a set of low level HTTP transport components that can be used to build custom client and server side HTTP services with a minimal footprint. HttpCore supports two I/O models: blocking I/O model based on the classic Java I/O and non-blocking, event driven I/O model based on Java NIO

[Apache Log4j](#)

Apache Log4j 2 is an upgrade to Log4j that provides significant improvements over its predecessor, Log4j 1.x, and provides many of the improvements available in Logback while fixing some inherent problems in Logback's architecture.

[Apache Lucene, SOLR](#)

The Apache Lucene™ project develops open-source search software.

[Apache Tomcat, Tomcat Embed](#)

Apache Tomcat is an open source software implementation of the Java Servlet and JavaServer Pages technologies.

[Apache XBean :: Spring](#)

XBean :: Spring provides a schema-driven proprietary namespace handler for Spring contexts.

[Apache Xerces](#)

The Apache Xerces Project is responsible for software licensed to the Apache Software Foundation intended for the creation and maintenance of:

- XML parsers
- related software components

[Apache XML](#)

The Apache XML Project used to be the home for many XML-related subprojects, many of which have moved to top-level project status recently or are currently in migration. The Apache XML Project slowly transforms into an place where you can find pointers to XML-related projects here in The Apache Foundation.

Apache XML Commons External Components

The External Components portion of xml-commons contains interfaces that are defined by external standards organizations.

archiver

A streaming interface for archive generation.

archiver-utils

A streaming interface for archive generation.

array-tree-filter

Filter by keys in array tree

ASM

ASM is an all purpose Java bytecode manipulation and analysis framework. It can be used to modify existing classes or dynamically generate classes, directly in binary form. Provided common transformations and analysis algorithms allow to easily assemble custom complex transformations and code analysis tools.

AspectJ

AspectJ is a seamless aspect-oriented extension to the Java programming language. It is Java platform compatible easy to learn and use.

Async

Async is a utility module which provides straight-forward, powerful functions for working with asynchronous JavaScript.

async-validator

Validate form asynchronous. A variation of <https://github.com/freeformsystems/async-validate>

AWS SDK for Amazon SQS

The AWS Java SDK for Amazon SQS module holds the client classes that are used for communicating with Amazon Simple Queue Service.

AWS SDK for Java Core

The AWS SDK for Java - Core module holds the classes that are used by the individual service clients to interact with Amazon Web Services. Users need to depend on aws-java-sdk artifact for accessing individual client classes.

b4a

Buffer for Array (B4A) provides a set of functions for bridging the gap between the Node.js Buffer class and the Uint8Array class. A browser compatibility layer is also included, making it possible to use B4A in both Node.js and browsers without having to worry about whether you're dealing with buffers or typed arrays.

base64-js

base64-js does basic base64 encoding/decoding in pure JS.

bl

A Node.js Buffer list collector, reader and streamer thingy.

buffer

The buffer module from node.js, for the browser.

[buffer-crc32](#)

crc32 that works with binary data and fancy character sets, outputs buffer, signed or unsigned data and has tests.

[Byte Buddy](#)

Byte Buddy is a code generation and manipulation library for creating and modifying Java classes during the runtime of a Java application and without the help of a compiler.

[camelize](#)

recursively transform key strings to camel-case

[CDI APIs](#)

APIs for CDI (Contexts and Dependency Injection for Java).

[cglib](#)

cglib is a powerful, high performance and quality Code Generation Library, It is used to extend JAVA classes and implements interfaces at runtime.

[chalk](#)

Terminal string styling done right

[chardet](#)

Chardet is a character detection module written in pure JavaScript (TypeScript). Module uses occurrence analysis to determine the most probable encoding.

[Checker Qual](#)

Checker Qual is the set of annotations (qualifiers) and supporting classes used by the Checker Framework to type check Java source code.

[ClassMate](#)

ClassMate is a library for introspecting generic type information of types, member/static methods, fields. Especially useful for POJO/Bean introspection.

[classnames](#)

classnames is a simple JavaScript utility for conditionally joining classNames together.

[cli-cursor](#)

Toggle the CLI cursor. The cursor is gracefully restored if the process exits.

[cli-spinners](#)

70+ spinners for use in the terminal

[cli-width](#)

Get stdout window width, with four fallbacks, tty, output.columns, a custom environment variable and then a default.

[commander](#)

The complete solution for node.js command-line interfaces.

[CommandLineParser](#)

C# command line parser that brings standardized *nix getopt style, for .NET. Includes F# support.

[compress-commons](#)

Compress Commons is a library that defines a common interface for working with archive formats within node.

[Config \(Typesafe\)](#)

A configuration library for JVM languages.

[crc-32](#)

Standard CRC-32 algorithm implementation in JS (for the browser and nodejs). Emphasis on correctness, performance, and IE6+ support.

[crc32-stream](#)

crc32-stream is a streaming CRC32 checksumer. It uses the crc module behind the scenes to reliably handle binary data and fancy character sets. Data is passed through untouched.

[cross-spawn](#)

A cross platform solution to node's spawn and spawnSync.

[css-color-keywords](#)

A list of all CSS color keywords.

[css-to-react-native](#)

Convert CSS text to a React Native stylesheet object

[csstype](#)

Strict TypeScript and Flow types for style based on MDN data

[date-fns](#)

date-fns provides the most comprehensive, yet simple and consistent toolset for manipulating JavaScript dates in a browser & Node.js

[dayjs](#)

Day.js is a minimalist JavaScript library that parses, validates, manipulates, and displays dates and times for modern browsers with a largely Moment.js-compatible API. If you use Moment.js, you already know how to use Day.js.

[decamelize](#)

Convert a camelized string into a lowercased one with a custom separator. Example: unicornRainbow → unicorn_rainbow

[diff](#)

A JavaScript text differencing implementation.

[DITA-OT](#)

The DITA Open Toolkit is a Java-based implementation of the OASIS DITA Technical Committee's specification for DITA DTDs and schemas. It contains ANT, SAXON,...

[DockPanel Suite](#)

.Net Docking Library for Windows Forms

[dom4j](#)

dom4j is an easy to use, open source library for working with XML, XPath and XSLT on the Java platform using the Java Collections Framework and with full support for DOM, SAX and JAXP.

[dsinfo](#)

The dsinfo library enables you to easily use Scala-side information in implementations of embedded (internal) domain-specific languages. dsinfo is implemented using Scala macros which are an experimental feature of Scala 2.10 and 2.11.

[dsprofile](#)

The dsprofile library provides general facilities to implement domain-specific profiling in Scala and Java programs.

[edtFTPj/Free](#)

Free Java FTP library gives Java developers extensive FTP functionality.

[Ehcache](#)

Ehcache is an open source, standards-based cache for boosting performance, offloading your database, and simplifying scalability. It's the most widely-used Java-based cache because it's robust, proven, and full-featured. Ehcache scales from in-process, with one or more nodes, all the way to mixed in-process/out-of-process configurations with terabyte-sized caches.

[Elasticsearch RESTful client](#)

A RESTful client for the Elasticsearch search engine.

[emoji-regex](#)

emoji-regex offers a regular expression to match all emoji symbols and sequences (including textual representations of emoji) as per the Unicode Standard. It's based on emoji-test-regex-pattern, which generates (at build time) the regular expression pattern based on the Unicode Standard. As a result, emoji-regex can easily be updated whenever new emoji are added to Unicode.

[Error Prone](#)

Error Prone is a static analysis tool for Java that catches common programming mistakes at compile-time.

[excss](#)

ExCSS (Pronounced Excess) is a CSS 2.1 and CSS 3 parser for .NET. The goal of ExCSS is to make it easy to read and parse stylesheets into a friendly object model with full LINQ support.

[external-editor](#)

A node module to edit a string with a users preferred text editor using \$VISUAL or \$ENVIRONMENT.

[fast-fifo](#)

A fast fifo implementation similar to the one powering nextTick in Node.js core. Uses a linked list of growing fixed sized arrays to implement the FIFO to avoid allocating a wrapper object for each item.

[FastInfoSet](#)

Fast InfoSet (or FI) is an international standard that specifies a binary encoding format for the XML Information Set (XML Infoset) as an alternative to the XML document format. It aims to provide more efficient serialization than the text-based XML format.

[Fast Serialization](#)

Fast Serialization reimplements Java Serialization with focus on speed (up to 10 times faster), size and compatibility. This allows the use of FST with minimal code change.

[figures](#)

Unicode symbols with fallbacks for older terminals

Fizzler

Fizzler is a W3C Selectors parser and generic selector framework for document hierarchies.

fn-name

Get the name of a named function. There is a name property on functions, but it's not supported in all browsers. This module tries that property then falls back to extracting the name from the function source.

Font Awesome

Font Awesome gives you scalable vector icons that can instantly be customized - size, color, drop shadow, and anything that can be done with the power of CSS.

Fonto Editor

Fonto is an online XML editor designed for people with no knowledge of XML or any other technology that comes with structured content authoring.

fs-extra

fs-extra adds file system methods that aren't included in the native fs module and adds promise support to the fs methods. It also uses graceful-fs to prevent EMFILE errors. It should be a drop in replacement for fs.

fs.realpath

A backwards-compatible fs.realpath for Node v6 and above. In Node v6, the JavaScript implementation of fs.realpath was replaced with a faster (but less resilient) native implementation. That raises new and platform-specific errors and cannot handle long or excessively symlink-looping paths. This module handles those cases by detecting the new errors and falling back to the JavaScript implementation. On versions of Node prior to v6, it has no effect.

GeckoFX

Gecko is a free and open source layout engine used in many applications developed by the Mozilla Foundation and the Mozilla Corporation (notably the Firefox web browser).

geckofx45.64

library that allows embedding gecko in C# applications.

glob

glob functionality for node.js

globalize

JavaScript globalization and localization. Formats and parses strings, dates and numbers in over 350 cultures.

GNU Aspell

GNU Aspell is a Free and Open Source spell checker designed to eventually replace Ispell. It can either be used as a library or as an independent spell checker. Its main feature is that it does a superior job of suggesting possible replacements for a misspelled word than just about any other spell checker out there for the English language. Unlike Ispell, Aspell can also easily check documents in UTF-8 without having to use a special dictionary. Aspell will also do its best to respect the current locale setting. Other advantages over Ispell include support for using multiple dictionaries at once and intelligently handling personal dictionaries when more than one Aspell process is open at once.

Specifically we are using GNUASpell dictionaries for de-CH, de-DE, en-CA, en-GB, en-US, es-ES, fr-FR, fr-CH, nl-NL.

[google-code-prettify](#)

google-code-prettify is a Javascript module and CSS file that allows syntax highlighting in an html page.

[google-gson](#)

google-gson is a Java library to convert JSON to Java objects and vice-versa.

[Google Guava](#)

The Guava project contains several of Google's core libraries that we rely on in our Java-based projects: collections, caching, primitives support, concurrency libraries, common annotations, string processing, I/O, and so forth.

[Google J2ObjC](#)

J2ObjC is an open-source command-line tool from Google that translates Java source code to Objective-C for the iOS (iPhone/iPad) platform. This tool enables Java source to be part of an iOS application's build, as no editing of the generated files is necessary.

[graceful-fs](#)

graceful-fs functions as a drop-in replacement for the fs module, making various improvements. The improvements are meant to normalize behavior across different platforms and environments, and to make filesystem access more resilient to errors.

[GraphQL-Java](#)

The Java implementation of GraphQL.

[HdrHistogram](#)

A High Dynamic Range Histogram that supports recording and analyzing sampled data value counts across a configurable integer value range with configurable value precision within the range. Value precision is expressed as the number of significant digits in the value recording, and provides control over value quantization behavior across the value range and the subsequent value resolution at any given level.

[Hibernate](#)

Hibernate is a high-performance Object/Relational persistence and query service. The most flexible and powerful Object/Relational solution on the market, Hibernate takes care of the mapping from Java classes to database tables and from Java data types to SQL data types. It provides data query and retrieval facilities that significantly reduce development time. Hibernate's design goal is to relieve the developer from 95% of common data persistence-related programming tasks by eliminating the need for manual, hand-crafted data processing using SQL and JDBC.

[HK2 Framework](#)

HK2 is a light-weight and dynamic dependency injection framework.

[HSQldb \(HyperSQL DataBase\)](#)

HSQldb (HyperSQL DataBase) is the leading SQL relational database engine written in Java. It offers a small, fast multithreaded and transactional database engine with in-memory and disk-based tables and supports embedded and server modes. It includes a powerful command line SQL tool and simple GUI query tools.

[Hunspell](#)

Hunspell is the spell checker of LibreOffice, OpenOffice.org, Mozilla Firefox 3 & Thunderbird, Google Chrome, and it is also used by proprietary software packages, like Mac OS X, InDesign, MemoQ, Opera and Trados Studio.

[i18next-http-backend](#)

This is a simple i18next backend to be used in Node.js, in the browser and for Deno. It will load resources from a backend server using the XMLHttpRequest or the fetch API.

[i18next-intervalplural-postprocessor](#)

This is a i18next postProcessor enabling interval based plurals.

[iconv-lite](#)

Convert character encodings in pure javascript.

[IdentityModel](#)

A .NET standard helper library for claims-based identity, OAuth 2.0 and OpenID Connect.

[IdentityModel OidcClient](#)

A C#/NetStandard OpenID Connect Client Library for native Applications.

[ieee754](#)

Read/write IEEE754 floating point numbers from/to a Buffer or array-like object.

[inflight](#)

Add callbacks to requests in flight to avoid async duplication

[inherits](#)

Easy simple tiny inheritance in JavaScript

[inquirer](#)

A collection of common interactive command line user interfaces.

[InstallAnywhere](#)

InstallAnywhere is the leading multi-platform development solution for application producers who need to deliver a professional and consistent cross installation experience for physical, virtual and cloud environments. From a single project file and build environment, InstallAnywhere creates reliable installations for on-premises platforms - Windows, Linux, Apple OS X, Solaris, AIX, HP-UX, and IBM iSeries - and enables you to take existing and new software products to a virtual and cloud infrastructure.

[is-fullwidth-code-point](#)

Check if the character represented by a given Unicode code point is fullwidth

[is-interactive](#)

Check if stdout or stderr is interactive

[is-unicode-supported](#)

Detect whether the terminal supports Unicode

[Jackson tooling](#)

Inspired by the quality and variety of XML tooling available for the Java platform (StAX, JAXB, etc.), the Jackson is a multi-purpose Java library for processing JSON data format. Jackson aims to be the best possible combination of fast, correct, lightweight, and ergonomic components for developers.

[Jakarta Activation API](#)

The JavaBeans Activation Framework API JAR.

[Jakarta XML Bind API](#)

Jakarta's XML bind API.

[Java API for RESTful web services \(javax.ws.rs\)](#)

Java API for RESTful Web Services.

[JavaBeans Activation Framework](#)

With the JavaBeans Activation Framework standard extension, developers who use Java technology can take advantage of standard services to determine the type of an arbitrary piece of data, encapsulate access to it, discover the operations available on it, and to instantiate the appropriate bean to perform said operation(s).

[JavaBeans Validation](#)

Bean Validation (JSR-303) API.

[Javassist \(*Java Programming Assistant*\)](#)

Javassist (*Java Programming Assistant*) makes Java bytecode manipulation simple. It is a class library for editing bytecodes in Java; it enables Java programs to define a new class at runtime and to modify a class file when the JVM loads it. Unlike other similar bytecode editors, Javassist provides two levels of API: source level and bytecode level. If the users use the source-level API, they can edit a class file without knowledge of the specifications of the Java bytecode. The whole API is designed with only the vocabulary of the Java language. You can even specify inserted bytecode in the form of source text; Javassist compiles it on the fly. On the other hand, the bytecode-level API allows the users to directly edit a class file as other editors.

[javax.annotation](#)

JSR 250 Common Annotations For The Java Platform.

[javax.cache](#)

Caching Java API

[Javax Expression Language](#)

Expression Language Java API

[javax.inject](#)

Dependency Injection Java API

[javax.validation](#)

Bean Validation API

[javax.jms](#)

The Java Message Service (JMS) API is a messaging standard that allows application components based on the Java 2 Platform, Enterprise Edition (J2EE) to create, send, receive, and read messages. It enables distributed communication that is loosely coupled, reliable, and asynchronous.

[JAXB](#)

The goal of the JAXB project is to develop and evolve the code base for the Reference Implementation (RI) of JAXB, the Java Architecture for XML Binding. The JAXB specification is developed through the Java Community Process following the process described at jcp.org. This process involves an Expert Group with a lead that is responsible for delivering the specification, a reference implementation (RI) and a Technology Compatibility Kit (TCK). The primary goal of an RI is to support the development of the specification and to validate it. Specific RIs can have additional goals; the JAXB RI is a production-quality implementation that is used directly in a number of products by Oracle and other vendors.

JBoss Java Annotation Indexer (Jandex)

A Java Annotation Indexer for JBoss

JBoss Logging Framework

The JBoss Logging Framework.

jedis

A blazingly small and sane Redis Java client.

Jersey RESTful WS

Developing RESTful Web services that seamlessly support exposing your data in a variety of representation media types and abstract away the low-level details of the client-server communication is not an easy task without a good toolkit. In order to simplify development of RESTful Web services and their clients in Java, a standard and portable JAX-RS API has been designed. Jersey RESTful Web Services framework is open source, production quality, framework for developing RESTful Web Services in Java that provides support for JAX-RS APIs and serves as a JAX-RS (JSR 311 & JSR 339) Reference Implementation.

Jettison

Jettison is a collection of Java APIs (like STaX and DOM) which read and write JSON. This allows nearly transparent enablement of JSON based web services in services frameworks like CXF or XML serialization frameworks like XStream.

Jetty

The Jetty Web Server provides an HTTP server and Servlet container capable of serving static and dynamic content either from a standalone or embedded instantiations. Starting from Jetty version 7, the Jetty webserver and other core components are hosted by the Eclipse Foundation.

JLine

JLine is a Java library for handling console input. It is similar in functionality to BSD editline and GNU readline. People familiar with the readline/editline capabilities for modern shells (such as bash and tcsh) will find most of the command editing features of JLine to be familiar.

JMESPath Java

JMESPath is a query language for JSON. You can extract and transform elements from a JSON document. This is a Java implementation

Joda-Convert

Joda-Convert provides a small set of classes to provide round-trip conversion between Objects and Strings. It does not tackle the wider problem of Object to Object transformation.

Joda-Time

Joda-Time provides a quality replacement for the Java *date* and *time* classes. The design allows for multiple *calendar* systems, while still providing a simple API. The 'default' calendar is the http://www.joda.org/joda-time/cal_iso.html standard which is used by XML. The Gregorian, Julian, Buddhist, Coptic, Ethiopic and Islamic systems are also included, and we welcome further additions. Supporting classes include time zone, duration, format and parsing.

JOL (Java Object Layout)

JOL (Java Object Layout) is the tiny toolbox to analyze object layout schemes in JVMs. These tools are using Unsafe, JVMTI, and Serviceability Agent (SA) heavily to decoder the *actual* object layout, footprint, and references.

jQuery

jQuery is a fast, small, and feature-rich JavaScript library. It makes things like HTML document traversal and manipulation, event handling, animation, and Ajax much simpler with an easy-to-use API that works across a multitude of browsers. With a combination of versatility and extensibility, jQuery has changed the way that millions of people write JavaScript.

jQuery CheckBoxTree

A jQuery based checkbox tree plugin that displays your hierarchical data in a tree structure with checkboxes.

jquery-cookie

jQuery plugin for reading, writing and deleting cookies.

jquery.datatables

DataTables is a plug-in for the jQuery Javascript library. It is a highly flexible tool, based upon the foundations of progressive enhancement, which will add advanced interaction controls to any HTML table.

jquery.dataTables.columnFilter

Adds advanced filter capabilities to the DataTables. JS file.

jQueryFileUpload

File Upload widget with multiple file selection, drag&drop support, progress bar, validation and preview images, audio and video for jQuery.

jquery.TypeScript.DefinitelyTyped

TypeScript Definitions (d.ts) for jquery.

jQuery.Gantt

Draw Gantt charts with the famous jQuery ease of development.

jQuery Highlight

Highlights the search keywords/terms in a preview.

jQuery UI

jQuery UI is a set of user interface interactions, effects, widgets, and themes built on top of the jQuery JavaScript Library.

json2mq

Generate media query string from JSON or javascript object

jsonfile

Easily read/write JSON files in Node.js. Note: this module cannot be used in the browser.

JSON-js

JSON is a light-weight, language independent, data interchange format. See <http://www.JSON.org> / The files in this collection implement JSON encoders/decoders in JavaScript. JSON became a built-in feature of JavaScript when the ECMAScript Programming Language Standard - Fifth Edition was adopted by the ECMA General Assembly in December 2009. Most of the files in this collection are for applications that are expected to run in obsolete web browsers. For most purposes, json2.js is the best choice.

[Json.NET](#)

Json.NET is a popular high-performance JSON framework for .NET.

[jsoup](#)

jsoup is a Java library for working with real-world HTML. It provides a very convenient API for extracting and manipulating data, using the best of DOM, CSS, and jquery-like methods.

[JTA \(Java Transaction API\)](#)

The `javax.transaction` package. It is appropriate for inclusion in a classpath, and may be added to a Java 2 installation.

[Kiama](#)

The Kiama test library contains a collection of examples, tests that use those examples, and useful test support code.

[Knockout JavaScript library](#)

Knockout is a JavaScript library that helps you to create rich, responsive display and editor user interfaces with a clean underlying data model. Any time you have sections of UI that update dynamically (e.g., changing depending on the user's actions or when an external data source changes), KO can help you implement it more simply and maintainably.

[Kryo](#)

Kryo is a fast and efficient binary object graph serialization framework for Java. The goals of the project are high speed, low size, and an easy to use API. The project is useful any time objects need to be persisted, whether to a file, database, or over the network.

Kryo can also perform automatic deep and shallow copying/cloning. This is direct copying from object to object, not object to bytes to object.

[kXML 2](#)

kXML is a small XML pull parser, specially designed for constrained environments such as Applets, Personal Java or MIDP devices. In contrast to kXML 1, kXML 2 is based on the XML pull API.

[LatencyUtils](#)

The LatencyUtils package includes useful utilities for tracking latencies. Especially in common in-process recording scenarios, which can exhibit significant coordinated omission sensitivity without proper handling.

[lazystream](#)

Create streams lazily when they are accessed (read from/written to).

[lodash.isequalwith](#)

A modern JavaScript utility library delivering modularity, performance, & extras.

[lodash-es](#)

A modern JavaScript utility library delivering modularity, performance, & extras.

[Logback](#)

Logback is intended as a successor to the popular log4j project, picking up where log4j leaves off.

[log-symbols](#)

Colored symbols for various log levels

[loose-envify](#)

Fast (and loose) selective process.env replacer using js-tokens instead of an AST. Works just like envify but much faster.

[MapStruct](#)

MapStruct is a code generator that greatly simplifies the implementation of mappings between Java bean types based on a convention over configuration approach. The generated mapping code uses plain method invocations and thus is fast, type-safe and easy to understand.

[MathJAX](#)

MathJax is an open-source JavaScript display engine for LaTeX, MathML, and AsciiMath notation that works in all modern browsers. It was designed with the goal of consolidating the recent advances in web technologies into a single, definitive, math-on-the-web platform supporting the major browsers and operating systems.

[Micrometer](#)

Micrometer provides a simple facade over the instrumentation clients for the most popular monitoring systems, allowing you to instrument your JVM-based application code without vendor lock-in. Think SLF4J, but for metrics.

[Microsoft.Bcl.AsyncInterfaces](#)

Provides the `IAsyncEnumerable<T>` and `IAsyncDisposable` interfaces and helper types for .NET Standard 2.0. This package is not required starting with .NET Standard 2.1 and .NET Core 3.0.

[microsoft.extensions.configuration.abstractions](#)

Provides abstractions of key-value pair based configuration. Interfaces defined in this package are implemented by classes in `Microsoft.Extensions.Configuration` and other configuration packages.

[microsoft.extensions.dependencyinjection](#)

Supports the dependency injection (DI) software design pattern which is a technique for achieving Inversion of Control (IoC) between classes and their dependencies.

[microsoft.extensions.dependencyinjection.abstractions](#)

Supports the lower-level abstractions for the dependency injection (DI) software design pattern which is a technique for achieving Inversion of Control (IoC) between classes and their dependencies.

[microsoft.extensions.logging](#)

`Microsoft.Extensions.Logging` is combined with a core logging abstraction under `Microsoft.Extensions.Logging.Abstractions`. This abstraction is available in our basic built-in implementations like console, event log, and debug (`Debug.WriteLine`) logging.

[microsoft.extensions.logging.abstractions](#)

`Microsoft.Extensions.Logging.Abstractions` provides abstractions of logging. Interfaces defined in this package are implemented by classes in `Microsoft.Extensions.Logging` and other logging packages. This package includes a logging source generator that produces highly efficient and optimized code for logging message methods.

[microsoft.extensions.options](#)

Microsoft.Extensions.Options provides a strongly typed way of specifying and accessing settings using dependency injection and acts as a bridge between configuration, DI, and higher level libraries. This library is the glue for how an app developer uses DI to configure the behavior of a library like HttpClient Factory. This also enables user to get a strongly-typed view of their configuration. Within this package, you'll find an options validation source generator that generates exceptionally efficient and optimized code for validating options.

[microsoft.extensions.primitives](#)

Microsoft.Extensions.Primitives contains isolated types that are used in many places within console or ASP.NET Core applications using framework extensions.

[microsoft.extensions.dependencyinjection](#)

Supports the dependency injection (DI) software design pattern which is a technique for achieving Inversion of Control (IoC) between classes and their dependencies.

[microsoft.identitymodel.abstractions](#)

A package containing thin abstractions for Microsoft.IdentityModel.

[microsoft.identitymodel.jsonwebtokens](#)

Includes types that provide support for creating, serializing and validating JSON Web Tokens. This is a newer, faster version of System.IdentityModel.Tokens.Jwt that has additional functionality.

[microsoft.identitymodel.logging](#)

Includes Event Source based logging support.

[microsoft.identitymodel.protocols](#)

Provides base protocol support for OpenIdConnect and WsFederation.

[microsoft.identitymodel.protocols.openidconnect](#)

Includes types that provide support for OpenIdConnect protocol.

[microsoft.identitymodel.tokens](#)

Includes types that provide support for SecurityTokens, Cryptographic operations: Signing, Verifying Signatures, Encryption.

[Microsoft JDBC Driver for SQL Server](#)

Microsoft provides a Java Database Connectivity (JDBC) driver for use with SQL Server, and Azure SQL Database. The driver provides Java database connectivity from any Java application, application server, or Java-enabled applet. This driver is a Type 4 JDBC driver that provides database connectivity through the standard JDBC application program interfaces (APIs).

[microsoft-windowsapicodepack-core](#)

This is a fork of the Microsoft Windows API Code Pack, based on a repository created by Aybe. Due to the lack of updates to the original package, this fork was created to include all open pull requests on the original repository, apply fixes and add support for all current .NET Framework and .NET Core versions.

[microsoft-windowsapicodepack-shell](#)

This is a fork of the Microsoft Windows API Code Pack, based on a repository created by Aybe. Due to the lack of updates to the original package, this fork was created to include all open pull requests on the original repository, apply fixes and add support for all current .NET Framework and .NET Core versions.

[minimatch](#)

A minimal matching utility. This is the matching library used internally by npm. It works by converting glob expressions into JavaScript RegExp objects.

[minimist](#)

parse argument options

[Minlog](#)

MinLog is a tiny Java logging library.

[mute-stream](#)

Bytes go in, but they don't come out (when muted). This is a basic pass-through stream, but when muted, the bytes are silently dropped, rather than being passed through.

[MXP1](#)

MXP1 is a stable XmlPull parsing engine that is based on ideas from XPP and in particular XPP2 but completely revised and rewritten to take the best advantage of latest JIT JVMs such as Hotspot in JDK 1.4+.

[nanoid](#)

A tiny (124 bytes), secure, URL-friendly, unique string ID generator for JavaScript

[neo-async](#)

Neo-Async is thought to be used as a drop-in replacement for Async, it almost fully covers its functionality and runs faster

[NHunspell](#)

NHunspell brings the spell checking, hyphenation and thesaurus to the Microsoft® .NET Framework. NHunspell is C# library and wraps native libraries for Hunspell, Hyphen and MyThes. One design goal of this library and wrapper is to keep the source code of the included libraries as unmodified as possible. New versions of the base libraries can therefore easily adopted to NHunspell.

The integrated libraries are used in OpenOffice and they work with the dictionaries published on OpenOffice.org.

[NLog](#)

NLog is a flexible and free logging platform for various .NET platforms, including .NET standard. NLog makes it easy to write to several targets. (database, file, console) and change the logging configuration on-the-fly.

[nlog.extensions.logging](#)

NLog.Extensions.Logging makes it possible to use NLog together with Microsoft ILogger-abstraction and Dependency Injection.

[NLog.WindowsEventLog](#)

NLog.WindowsEventLog provides access to the EventLog-target for NetStandard

[normalize-path](#)

Normalize slashes in a file path to be posix/unix-like forward slashes. Also condenses repeat slashes to a single slash and removes and trailing slashes, unless disabled.

[Objenesis](#)

Objenesis is a small Java library that serves one purpose: to instantiate a new object of a particular class.

okhttp

An HTTP+HTTP/2 client for Android and Java applications.

okio

A modern I/O API for Java.

once

Run a function exactly one time

ora

Elegant terminal spinner

Oracle JDBC Drivers

Drivers used for making a JDBC connection from Java to an Oracle database.

Oracle PKI (Public Key Infrastructure)

Oracle public key infrastructure (PKI) is used by Oracle Enterprise Security Manager, LDAP-enabled Oracle Enterprise Manager, Oracle's Secure Socket Layer (SSL) authentication, Oracle Database, and Oracle Application Server.

Oracle Security Developer Tools (OSDT)

Oracle Security Developer Tools provide you with the cryptographic building blocks necessary for developing robust security applications, ranging from basic tasks like secure messaging to more complex projects such as securely implementing a service-oriented architecture. The tools build upon the core foundations of cryptography, public key infrastructure, web services security, and federated identity management.

path-key

Get the PATH environment variable key cross-platform

Path-to-RegExp

Turn a path string such as `/user/:name`` into a regular expression.

PATRICIA Trie in Java

An implementation of the Practical Algorithm to Retrieve Information Coded in Alphanumeric (PATRICIA).

picocolors

The tiniest and the fastest library for terminal output formatting with ANSI colors.

Postal.Mvc5

Generate emails using ASP.NET MVC views

postcss

PostCSS is a tool for transforming styles with JS plugins. These plugins can lint your CSS, support variables and mixins, transpile future CSS syntax, inline images, and more.

postcss-value-parser

Transforms CSS declaration values and at-rule parameters into a tree of nodes, and provides a simple traversal API.

Project Reactor

Reactor is a fourth-generation Reactive library for building non-blocking applications on the JVM based on the Reactive Streams Specification.

[property-expr](#)

Tiny property path utilities, including path parsing and metadata and deep property setters and getters

[PS Cmdlet Help Editor](#)

PowerShell Cmdlet Help Editor is the tool that helps you to create and edit XML-based help files for your PowerShell modules and PSSnap-Ins.

[qrcode.react](#)

A React component to generate QR codes for rendering to the DOM.

[queue-tick](#)

Next tick shim that prefers process.nextTick over queueMicrotask for compat

[rc-align](#)

React Align Component. Wrapper around <https://github.com/yiminghe/dom-align>.

[rc-cascader](#)

React Cascader Component. Cascade select in one box

[rc-checkbox](#)

Checkbox ui component for react.

[rc-collapse](#)

React Collapse / Accordion. rc-collapse ui component for react

[rc-dialog](#)

react dialog component

[rc-drawer](#)

React Drawer

[rc-dropdown](#)

react dropdown component

[rc-field-form](#)

React Performance First Form Component.

[rc-image](#)

React Image.

[rc-input](#)

React Input Component

[rc-input-number](#)

React Input Number

[rc-mentions](#)

React Mentions

[rc-menu](#)

React menu component. port from <https://github.com/kissyteam/menu>

[rc-motion](#)

React lifecycle controlled motion library.

rc-notification

React Notification UI Component

rc-overflow

Auto collapse box when overflow

rc-pagination

React Pagination Component.

rc-picker

All Date Pickers you need.

rc-progress

React Progress Bar

rc-rate

React Rate Component

rc-resize-observer

Resize observer for React.

rc-segmented

React Segmented Control.

rc-select

React Select

rc-slider

Slider UI component for React

rc-steps

React steps component.

rc-switch

Switch ui component for react.

rc-table

React table component with useful functions.

rc-tabs

React Tabs component.

rc-textarea

Pretty Textarea react component used in ant.design.

rc-tooltip

React Tooltip

rc-tree

Tree component.

rc-tree-select

React TreeSelect Component

rc-trigger

React Trigger Component

[rc-upload](#)

React Upload

[rc-util](#)

Common Utils For React Component.

[rc-virtual-list](#)

React Virtual List Component which worked with animation.

[react-dom](#)

React package for working with the DOM.

[react-fast-compare](#)

The fastest deep equal comparison for React.

[react-i18next](#)

react-i18next implements internationalization for react using the i18next i18n ecosystem.

[react-is](#)

React is a JavaScript library for building user interfaces.

[Reactive Streams](#)

A Protocol for Asynchronous Non-Blocking Data Sequence

[ReactJS](#)

React is a JavaScript library for building user interfaces.

[Reactor Core](#)

Reactor Core is a non-blocking reactive foundation for the JVM.

[react-popper](#)

Official React library to use Popper, the positioning library

[react-scrollbar-size](#)

React hook to calculate the size of browser scrollbars.

[readable-stream](#)

Node-core streams for userland. This package is a mirror of the streams implementations in Node.js 18.19.0.

[readdir-glob](#)

Recursive fs.readdir with streaming API and glob filtering.

[Red Hat Linux](#)

Red Hat Enterprise Linux OpenStack Platform delivers an integrated foundation to create, deploy, and scale a secure and reliable public or private OpenStack cloud. Red Hat Enterprise Linux OpenStack Platform combines the world's leading enterprise Linux and the fastest-growing cloud infrastructure platform to give you the agility to scale and quickly meet customer demands without compromising on availability, security, or performance.

[ReflectASM](#)

ReflectASM is a very small Java library that provides high performance reflection by using code generation. An access class is generated to set/get fields, call methods, or create a new instance. The access class uses bytecode rather than Java's reflection, so it is much faster. It can also access primitive fields via bytecode to avoid boxing.

[resolve-pathname](#)

Resolve URL pathnames using JavaScript

[run-async](#)

Utility method to run function either synchronously or asynchronously using the common ``this.async()`` style.

[Rx .NET](#)

Reactive Extensions for .NET library used to validate entered values

[Scala](#)

The Scala programming language fuses object-oriented and functional programming in a statically typed programming language. It is aimed at the construction of components and component systems.

[Scallop](#)

Scallop is a command line parser.

[scheduler](#)

React is a JavaScript library for building user interfaces.

[scroll-into-view-if-needed](#)

`Element.scrollIntoView` ponyfills for things like "if-needed" and "smooth"

[shallowequal](#)

Performs a shallow equality comparison between two values (i.e. value and other) to determine if they are equivalent.

[shebang-command](#)

Get the command from a shebang

[SitemapGen4j](#)

SitemapGen4j is a library to generate XML sitemaps in Java.

[SLF4J](#)

The Simple Logging Facade for Java (SLF4J) serves as a simple facade or abstraction for various logging frameworks (e.g. java.util.logging, logback, log4j) allowing the end user to plug in the desired logging framework at deployment time.

[SnakeYAML](#)

YAML is a data serialization format designed for human readability and interaction with scripting languages. SnakeYAML is a YAML parser and emitter for the Java programming language.

[SNMP4j](#)

SNMP4J is an enterprise class free open source and state-of-the-art SNMP implementation for Java™ 2SE 1.4 or later. SNMP4J supports command generation (managers) as well as command responding (agents). Its clean object oriented design is inspired by SNMP++, which is a well-known SNMPv1/v2c/v3 API for C++.

[source-map](#)

This is a library to generate and consume the source map format described here.

[source-map-js](#)

Difference between original source-map: TL;DR: it's fork of original source-map@0.6, but with performance optimizations.

[SpringFox](#)

Automated JSON API documentation for API's built with Spring.

[Spring Framework](#)

The Spring Framework provides a comprehensive programming and configuration model for modern Java-based enterprise applications - on any kind of deployment platform. A key element of Spring is infrastructural support at the application level: Spring focuses on the "plumbing" of enterprise applications so that teams can focus on application-level business logic, without unnecessary ties to specific deployment environments.

[StAX](#)

StAX is a standard XML processing API that allows you to stream XML data from and to your application. This StAX implementation is the standard pull parser implementation for JSR-173 specification.

[streamx](#)

An iteration of the Node.js core streams with a series of improvements.

[string_decoder](#)

Node-core v8.9.4 string_decoder for userland

[strip-ansi](#)

Strip ANSI escape codes from a string

[styled-components](#)

styled-components are visual primitives for the component age, enabling you to use ES6 and CSS to style your apps.

[supports-color](#)

Detect whether a terminal supports color

[SVG.NET](#)

Public fork of the C# SVG rendering library. This started out as a minor modification to enable the writing of proper SVG strings. But now after almost two years we have so many fixes and improvements that we decided to share our current codebase to the public in order to improve it even further.

[Swagger](#)

Swagger is a simple yet powerful representation of your RESTful API. With the largest ecosystem of API tooling on the planet, thousands of developers are supporting Swagger in almost every modern programming language and deployment environment. With a Swagger-enabled API, you get interactive documentation, client SDK generation and discoverability.

[Swashbuckle.Core](#)

Seamlessly adds a Swagger to WebApi projects.

[synchronous-promise](#)

A prototypical animal which looks like an A+ Promise but doesn't defer immediately, so can run synchronously, for testing

[system.configuration.configurationmanager](#)

Provides types that support using XML configuration files (app.config). This package exists only to support migrating existing .NET Framework code that already uses System.Configuration. When writing new code, use another configuration system instead, such as Microsoft.Extensions.Configuration.

[system.diagnostics.diagnosticsource](#)

Provides Classes that allow you to decouple code logging rich (unserializable) diagnostics/telemetry (e.g. framework) from code that consumes it (e.g. tools)

[system.diagnostics.eventlog](#)

This package provides types that allow applications to interact with the Windows Event Log service. When an error occurs in a Windows machine, the system administrator or support representative must determine what caused the error, attempt to recover any lost data, and prevent the error from recurring. It is helpful if applications, the operating system, and other system services record important events, such as low-memory conditions or excessive attempts to access a disk. The system administrator can then use the Windows Event Log to help determine what conditions caused the error and identify the context in which it occurred.

[system.identitymodel.tokens.jwt](#)

Includes types that provide support for creating, serializing and validating JSON Web Tokens. As of IdentityModel 7x, this is a legacy tool that should be replaced with Microsoft.IdentityModel.JsonWebTokens.

[system.memory](#)

Provides types for efficient representation and pooling of managed, stack, and native memory segments and sequences of such segments, along with primitives to parse and format UTF-8 encoded text stored in those memory segments.

[system.runtime.compilerservices.unsafe](#)

Provides the System.Runtime.CompilerServices.Unsafe class, which provides generic, low-level functionality for manipulating pointers.

[system.security.accesscontrol](#)

Provides base classes that enable managing access and audit control lists on securable objects.

[system.security.permissions](#)

Provides types supporting Code Access Security (CAS).

[system.security.principal.windows](#)

Provides classes for retrieving the current Windows user and for interacting with Windows users and groups.

[system.servicemodel.http](#)

Provides the types that permit SOAP messages to be exchanged using Http (example: BasicHttpBinding).

[system.servicemodel.primitives](#)

Provides the common types used by all of the WCF libraries.

[system.text.encodings.web](#)

Provides types for encoding and escaping strings for use in JavaScript, HyperText Markup Language (HTML), and uniform resource locators (URL).

[system.text.json](#)

Provides high-performance and low-allocating types that serialize objects to JavaScript Object Notation (JSON) text and deserialize JSON text to objects, with UTF-8 support built-in. Also provides types to read and write JSON text encoded as UTF-8, and to create an in-memory document object model (DOM), that is read-only, for random access of the JSON elements within a structured view of the data.

tar-stream

tar-stream is a streaming tar parser and generator.

Thinkecture IdentityModel

Helpers and client libraries for OpenID Connect, OAuth 2.0 and claims-based Identity.

Thinkecture IdentityServer

Front-end Secure Token Service to serve SAML tokens.

throttle-debounce

Throttle and debounce functions.

tmp

Temporary file and directory creator for node.js

TwelveMonkeys Common

TwelveMonkeys Common library contains common utility classes relating to languages, I/O and images.

TwelveMonkeys ImageIO

TwelveMonkeys ImageIO is a collection of plugins and extensions for Java's ImageIO. These plugins extends the number of image file formats supported in Java, using the `javax.imageio.*` package. The main purpose of this project is to provide support for formats not covered by the JRE itself.

TXW2

TXW is a library that allows you to write XML documents.

ua-parser

A multi-language port of Browserscope's user agent parser.

universalify

Make a callback- or promise-based function support both promises and callbacks.

use-sync-external-store

React is a JavaScript library for building user interfaces.

util-deprecate

The Node.js `util.deprecate()` function with browser support

valid-filename

Check if a string is a valid filename

value-equal

value-equal determines if two JavaScript values are equal using `Object.prototype.valueOf`.

warning

A mirror of Facebook's Warning

wcwidth

Port of C's `wcwidth()` and `wcswidth()`

WebGrease

Web Grease is a suite of tools for optimizing javascript, css files and images.

which

Like which(1) unix command. Find the first instance of an executable in the PATH.

WiX

The WiX toolset builds Windows installation packages from XML source code. The tool-set integrates seamlessly into build processes.

Woodstox

Woodstox is a high-performance validating namespace-aware StAX-compliant (JSR-173) Open Source XML-processor written in Java.

wordwrap

Wrap your words.

wrap-ansi

Wordwrap a string with ANSI escape codes

wrappy

Callback wrapping utility

Xalan-Java

Xalan-Java is an XSLT processor for transforming XML documents into HTML, text, or other XML document types. It implements XSL Transformations (XSLT) Version 1.0 and XML Path Language (XPath) Version 1.0 and can be used from the command line, in an applet or a servlet, or as a module in other program.

Xerces Java Parser

The Xerces Java Parser 1.4.4 supports the XML 1.0 recommendation and contains advanced parser functionality, such as support for the W3C's XML Schema recommendation version 1.0, DOM Level 2 version 1.0, and SAX Version 2, in addition to supporting the industry-standard DOM Level 1 and SAX version 1 APIs.

XML Pull Parsing

An XML Pull Parsing API.

XStream

XStream is a simple library to serialize objects to XML and back again.

XULRunner

XULRunner is a runtime environment developed by the Mozilla Foundation to provide a common back-end for previewing.

zip-stream

zip-stream is a streaming zip archive generator based on the ZipArchiveOutputStream prototype found in the compress-commons project.

Customer support

To contact Technical Support, connect to the Customer Support Web Portal at <https://gateway.sdl.com> and log a case for your RWS product. You need an account to log a case. If you do not have an account, contact your company's RWS Support Account Administrator.

2

Installing Content Manager

This section explains how to install the Content Manager application, Content Manager database and Content Manager client tools, and how to enable the other Tridion Docs capabilities.

Content Manager requirements

All requirements for the Content Manager application, web, and batch servers are described.

Content Manager hardware requirements

Check the hardware requirements.

Hardware

The performance of Content Manager depends primarily on the CPU power and the I/O characteristics of the hardware. High CPU power is needed to allow the system to make calculations on-the-fly, e.g. for publishing. The I/O performance largely influences the system's speed to gather and assemble information from the database to serve user requests. Content Manager imposes no specific requirements for data storage, as it holds generic versions that become specific versions by calculation on a user's request.

The hardware required for a specific Content Manager implementation depends on the specific requirements and settings of the project (for example, the number of concurrent users). The exact definition of the hardware requirements is typically done at the beginning of the project.

Database

The database server may be on any platform supported by the database vendor. Hardware and platform requirements for the database server should be obtained from the database vendor. The specifications supplied by Content Manager should be checked against the specifications supplied by the database vendor for the current hardware on which it is installed.

An example Microsoft Windows server machine could minimally have the following specifications:

- CPU: dual core contemporary CPU
- Internal Memory: 8 GB RAM

Database storage demands must account for the following:

- All XML content and related metadata.
- All images.
- Published output (e.g. PDF, CHM...).

As a rule of thumb, multiply the size of all images by 3 to get an estimate of the starting size for your database. A normal documentation project can use 100 GB for its storage needs for about 2 to 3 years.

Web and Application layer

The server can be on a single system. However, for performance reasons it is advised to scale and have redundancy over multiple servers. The scaling introduction included in Tridion Docs documentation helps you determine the setup. Due to the many setup variations, you may want to contact the support team to discuss your specifics.

Minimum server configuration: A recent quad core system(s) containing 8 GB of RAM or more. Virtualized environments are supported if they are guaranteed to behave like a Windows OS installed on a physical machine. If performance is or becomes an issue, you are advised to use physical servers.

Storage demands: The consumers of storage are the actual installed Content Manager software components, the full-text-index collection, exported, and published content. Considering a normal documentation project, with an initial database reservation of 100 GB, the server should have at least 50 GB storage capacity. The typical setup is two servers, one handling the synchronous operations and one server handling the asynchronous/background operations. Initially you can start with one server handling all operations; we then suggest a dual CPU server. A second server can be added quite easily afterwards if load needs to be reduced on the primary server.

Client requirements

Client machines running desktop applications such as Publication Manager should have at least a 2.0 GHz CPU and 4 GB RAM.

Network requirements

Due to its stateless model, Content Manager passes large quantities of data. A 10 Mbit network connection provides a more than acceptable throughput.

Content Manager software requirements

Information about third-party or client software that is packaged, configured and tested for this software version release.

The following overview includes information about:

- Third-party software that is configured or integrated in this server-side component release.
- Third-party software, such as the operating systems, databases, and runtimes that are quality-assurance tested.
- Client hardware and software compatibility.

The relation between the Authoring Bridge and the XML editors is not specified here. Installation packages for Authoring Bridge are not always available for all XML editors. Also third-party software such as authoring tools and databases have their specific requirements. Check out the third-party tools' documentation before installation.

This is a reference list not a task list. It specifies on which items our software relies. Some components might already be installed by other software. Some components may be needed only for certain features or configurations of Content Manager. Refer to the Content Manager installation or upgrade tasks to know which of the specified software you need to install.

Supported software versions

Note: Names, trademarks, designs, logos, service marks, intellectual property and so on, of the products shown are exclusive property of their respective owners.

Application server

- One of the following:
 - Microsoft Windows Server 2022
 - Microsoft Windows Server 2019 x64
- Microsoft Windows PowerShell 5.1 (part of Windows Management Framework 5.1)
- Microsoft .NET Framework 4.8
- ASP.NET Core Hosting Bundle, version 8 (includes the Microsoft .NET 8 LTS runtime)
- One of the following:
 - Oracle Java Development Kit 21.0.x x64 also known as Oracle JDK 21 LTS
 - Adoptium Eclipse Temurin 21.0.x x64 based on OpenJDK 21 LTS
 - Oracle Java Development Kit 17.0.x x64 also known as Oracle JDK 17 LTS
 - Adoptium Eclipse Temurin 17.0.x x64 based on OpenJDK 17 LTS
- DITA-OT 2.3

Note: Our standard Tridion Docs installation package holds a DITA Open Toolkit version.

- Microsoft XML Parser 6.0, 32-bit and 64-bit (pre-installed with Windows Server 2012R2 and 2016)
- Software for publishing, as required:
 - Java Help 2.0.05
 - HTML Help Workshop 1.3
 - AntennaHouse XSL Formatter 7.0

Database server

One of the following database systems:

- Oracle Database 19c (19.3.0.0)
- Microsoft SQL Server 2022
- Microsoft SQL Server 2019

Client

- One of the following operating systems:
 - Microsoft Windows 11
 - Microsoft Windows 10
- One of the following web browsers:
 - Microsoft Edge (Chromium-based; Microsoft's Modern Lifecycle Policy release update channel)
 - Google Chrome (Chromium-based; release update channel)
 - Mozilla Firefox (release update channel)

The browser must be configured to allow the following:

- Cookies
- Pop-up windows for Collective Spaces (that is, Draft Space and Review Space) when the application is called from Organize Space.
- A minimum resolution of 1024 x 768 pixels. The optimal resolution is 1280 x 1024 pixels or higher.
- The required DITA authoring tool:
 - JustSystems XMetaL 18.0 x64
 - JustSystems XMetaL 17.0 x64
 - Syncro Soft Oxygen XML Author 26.x x64
 - Syncro Soft Oxygen XML Author 25.x x64
 - Acrolinx 5.0

Only 64-bit mode for the editors is approved and qualified.

Although multiple third-party XML editors are supported, we recommend choosing and using a single third-party editor. RWS is not responsible for third-party editor XML and DITA handling; behavior may differ depending on the XML editor. If you use more than one editor, you may experience cross-compatibility issues related to DITA handling. If you decide to use multiple third-party XML editors and if you experience cross-compatibility issues with DITA handling, contact the XML editor vendor to address these issues.

Installer User Requirements

The users who can install Content Manager must have permissions and access as required.

An administrator user who has authorized access on the machines to be installed can install the Content Manager software. The user must be able to:

- log on to the machine and have full access to the file system
- alter the registry
- have full access to the Services and Internet Information Services

A database administrator must set up the Content Manager database. The user must be able to:

- create a database
- run scripts to set up the database

Platform virtualization

You can deploy Content Manager software in a virtual environment (such as VMWare ESX).

You can deploy Content Manager software in a virtual environment if both of the following conditions are true:

1. Content Manager supports the environment in its non-virtual form.
2. The platform vendor states that it supports the virtual form of this environment.

Note: If you run a software component in a virtual environment, the hardware recommendations listed for that software component may not apply. The recommendations listed apply to the software component if it is installed directly on such a hardware profile, and not to the software component installed in a virtual environment that itself runs on the recommended hardware profile.

For specific virtual platform support requests, contact the platform vendor. For specific hardware recommendations, contact your virtual hardware solution vendor to find out how the hardware recommendation for a direct installation translates into a hardware recommendation for a virtual installation.

Firewalls and ports

In specific cases, firewall and ports may require special attention.

Firewalls and ports are an important part of your installation environment. Normally the default settings do not interfere with a basic installation, but there is a variety of possibilities regarding network and firewall configurations. This list provides some of the most common points of attention and is by no means comprehensive.

The user responsible for the network setup knows all the items that should be checked in your environment and has access to the specific technical documentation. Details can be found in the *Advanced topics for installers* section.

SMTP

Simple Mail Transfer Protocol (SMTP) is the standard for e-mail transmissions across the internet.

Microsoft SQL Server

Microsoft SQL Server is the relational database management system (RDBMS) produced by Microsoft.

Oracle

Oracle Database, or simply Oracle, is the relational database management system (RDBMS) produced by Oracle Corporation.

HTTPS (SSL)

HTTPS is a URI scheme used to indicate a secure HTTP connection. It refers to the combination of a normal HTTP interaction over an encrypted Secure Sockets Layer (SSL).

Content Manager pre-installation tasks

Only if you are performing a first-time installation, perform the pre-installation tasks in this section. This ensures that you don't encounter issues when installing and configuring the mandatory Content Manager software components.

Enabling https on the IIS website

Content Manager requires that https is enabled on the IIS website that is used for Content Manager.

Before you begin

Follow this procedure on the main Content Manager server. After installing the certificate, you must bind the website to https (included in the last step below).

About this task

Before you can enable https on the Content Manager website you must first install a SSL certificate on the server. There are several ways to request and install a certificate:

- You can buy a certificate from a commercial certificate authority, for example, Verisign. These commercial CAs have online how-to help pages that guide you through the process of requesting a certificate and installing it.
- When your company has an internal Certificate Authority, you can request certificates yourself, or through your IT staff.
- Use the **Create Domain Certificate** in IIS. To do this follow the procedure below.

Procedure

1. Request and install the certificate.
 - a. In Internet Information Services (IIS) Manager, open: *ComputerName* > **Server Certificates**.
 - b. In the right **Actions** pane, click **Create Domain Certificate**. A Create Certificate window displays.
 - c. Add the necessary information to the fields in Create Certificate:
 - **Common name:** Enter the complete domain name of the URL to be used for this Content Manager. For example: *techdoccms.sdl.com*
 - **Organization:** enter your company name. For example: *SDL*

- **Organizational unit:** Enter the name of the department that is requesting the certificate. For example: *SDL IT*
 - **City, State & Country:** Enter the city, state & country where the company is located.
- d. Click **Next**.
An Online Certificate Authority window displays.
 - e. **Specify Online Certificate Authority** that you want to use by clicking **Select** to the right of the field.
-
- Note:** If the list for Certificate Authority is empty you cannot continue and you have to ask your IT department for instruction on how to continue.
-
- f. Enter a **Friendly Name**. The **Friendly Name** is a more user-friendly name for the certificate and is shown in several programs such as IIS.

You should see the requested certificate appearing in the IIS Server Certificates list, and you can now use it.
 - g. Click **Finish**.
2. Bind the website to https:
 - a. Right-click the IIS Website that will be used for Content Manager.
 - b. Select **Edit Bindings**.
 - c. Click **Add**.
 - In the **Type** field, select **https**.
 - In the **SSL certificate** field select the certificate that you requested and installed; select the **Friendly Name** specified in the previous step.
 - If the options **Disable HTTP/2** and **Disable OCSP Stapling** are present (depending on your version of Windows server), leave those box unchecked.
 - d. Click **OK**.

Defining the bindings in the target website

When using multiple websites IIS, the administrator of IIS should explicitly define the bindings in the target web site to ensure that the installation serves the requests that target it.

When an IIS has multiple websites it is not clear which website should serve the incoming request which can make the Content Manager installation unstable. On a IIS server with multiple websites, there has to be mechanism that guides IIS to the correct website. That mechanism is known as binding configuration. The binding works as a key in a Dictionary of Websites. So simply, IIS analyzes the request, figures out the key and then goes to the dictionary to find the proper website.

Note: Productions systems should always define the bindings on the website even if the website is unique on the IIS. When the bindings are explicitly defined on the website, the website is protected against any other request that was not intended to be served. This is another layer of protection for the website.

Assume the following values for Content Manager's `baseurl` and `localservicehostname`; that is, all requests that have the following host names that must be served by this website:

- `localhostname: example`
- `hostname: example.com`

In addition to the host names, the website must be able to serve the following schemas for both host names:

- `https-hostname`
- `https-localhostname` Example of end points that the website (IIS) is to serve:

- `https://example/ISHWS/WCF/API/Application.svc`
- `https://example.com/ISHWS/WCF/API/Application.svc`

Based on the above examples, to described the possible schema/hostname combinations for Content Manager, the IIS administrator needs to explicitly define bindings for the following combinations:

- `example.com`
- `example` Configuring the HTTPS bindings must be done by executing a command, such as:

```
%systemroot%\system32\inetsrv\APPCMD set site [WebSiteName]/bindings:https/*:443: [hostname]
```

Where you must replace the references to `[WebSiteName]` and `[hostname]` appropriately for your configuration and site. There are alternatives that are documented in the help of the commands.

For more information about adding a binding to a site, refer to:

- <https://learn.microsoft.com/en-us/iis/configuration/system.applicationHost/sites/site/bindings/binding>
- [https://learn.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2008-R2-and-2008/cc731692\(v=ws.10\)](https://learn.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2008-R2-and-2008/cc731692(v=ws.10))

Microsoft Windows Server

Additional installation and configuration requisites are described for the Content Manager product installation for the current supported versions of Microsoft Windows.

Content Manager must be installed on versions of Microsoft Windows Server referenced in the Content Manager software requirements list.

Note: Content Manager is qualified on an English version of our supported operating systems only. Other languages of these operational systems are not used for quality check purposes.

Establishing a dedicated system user

The Content Manager components need a dedicated Windows user with local administrator rights on each server to host all components, with the right region and language settings.

About this task

All Content Manager-related components should be run by a designated Windows user (also known as a Service Account) to be named `InfoShare`. This user lets you change user settings with little interference with the rest of the system. The user must be a Windows Domain user when using Microsoft ADFS as STS. Ask your Active Directory system administrator to create a service account.

Procedure

1. Create the local or domain `InfoShare` system user:

Note: If you have to configure multiple servers, we advise to create a domain user and make the user a local Administrator on each of the target machines as described here.

- a. Select **Server Manager** in the lower left corner.
- b. Select **Tools > Computer Management**.
- c. Open **Computer Management > System Tools > Local Users and Groups** then select **Users**.
- d. Open the **Action** menu and select **New user**.
- e. Enter `InfoShare` as the **User name**.
- f. Enter a **Full name** and a **Description**.
- g. Enter a **Password**. Enter the password again in the **Confirm password** field.
- h. Clear **User must change password at next logon** then select **User cannot change password** and **Password never expires**.
- i. Select **Create** and **Close**.
- j. Under **Local Users and Groups**, select **Groups**.
- k. Open the local **Administrators** group of the machine and add the `InfoShare` system user.
- l. Select **Apply**.

Note: Microsoft requires some registry keys to be write-enabled for transactions and more. The services, Message Queues, IIS Application Pools and Component Services Server Applications all run within this user's context.

2. To prevent service startup failues, allow the `InfoShare` user to run services:
 - a. As an administrator user, open **Administrative Tools** on your server and then double click on **Local Security Policy**.

- b. Open **Local Policies** then select **User Rights Assignment**.
 - c. Open **Log on as a service** then select **Add User or Group** and add the `InfoShare` user created above.
 - d. Select **OK** to activate the settings.
 - e. Open the **File** menu and select **Exit** to close the window.
3. Set the language and region of the `InfoShare` user:
 - a. Sign in to your system as the `InfoShare` user to validate the user account.
 - b. Open **Control Panel** and select **Region**.
A **Region** dialog opens.
 - c. Under **Format**, select **English (United Kingdom)**.
 - d. In the **Date and time formats** area, ensure that the fields are set as follows:

Field	Value
Short date	dd/MM/yyyy
Long date	dddd, d MMMM yyyy
Short time	HH:mm
Long time	HH:mm:ss
First day of week	Monday

4. Restart the server.

Changing the Local Group Policy

Set the group policy so that Windows does not forcefully unload the registry.

About this task

A new *User Profile Service* functionality built into the OS by default forces the unload of the user profile on Windows when the user logs off. This results in, for instance, a COM+ application to stop working on Windows Server when the identity user logs off and the COM+ application can no longer read registry keys in the profile of the identity user. The policy setting **Do not forcefully unload the user registry at user logoff** counters the default behavior of Windows. When enabled, Windows does not forcefully unload the registry and waits until no other process is using the user registry before it unloads it.

Procedure

1. As an Administrator user, start the **Windows PowerShell** (an icon can usually be found in the taskbar).
2. In the command prompt, type `gpedit.msc`.
A Local Group Policy Editor window displays.
3. In the left pane, open **Local Computer Policy > Computer Configuration > Administrative Templates > System > User Profiles**.
4. In the right pane, open **Do not forcefully unload the user registry at user logoff**.
5. In the resulting window, select the radio button **Enabled**.

6. Select **OK**.

Defining the location of the Oracle `tnsnames.ora` file

For an Oracle database, the system environment variable `TNS_ADMIN` must point to the correct location of the `tnsnames.ora` file.

Before you begin

To perform this task, you need to access the machine as an administrator.

Procedure

1. Open **Control Panel > System and Security > System > Advanced system settings > Environment Variables**.
2. Go to **System variables**.
3. Click **New** to add the extra environment variable:
 - **Variable name:** `TNS_ADMIN`
 - **Variable value:** The directory holding the `tnsnames.ora` file. For example `c:\oracle\common\admin`
4. Reboot the server to ensure that the new system environment variables are available for all processes.

Configuring HTTP Activation for WCF

Windows Communication Foundation (WCF) uses the listener adapter interface to communicate activation requests that are received over the non-HTTP protocols supported by WCF. To allow this, configure HTTP Activation.

Procedure

1. In the **Control Panel**, under the **Programs** heading, select **Turn windows features on or off**.
2. Select **Server Selection** in the list on the left.
3. Select the name of the server where the feature needs to be installed, in the center pane.
4. Select **Features** in the list on the left.
5. Open the **.NET Framework 4.X Features (Installed)** tree node then open **WCF services (Installed)**.
6. Select **HTTP Activation**.
7. If a popup window **You cannot install HTTP Activation unless the following role service or features are also installed** opens, then select the **Add Features** button to install the required features.
8. Use **Next** until the **Install** button becomes active.
9. Select **Install**.

Configuring IIS web services

Content Manager requires that you enable features of the IIS (Internet Information Services).

Before you begin

This is an optional component during a Windows installation, and is not installed by default during operating system setup.

For compatible software versions, check out the Content Manager software requirements.

Procedure

1. In the **Control Panel**, select **Programs and Features** then, on the left side of the window, **Turn Windows features on or off**.
2. In the Add roles and features window, select **Next**.
3. Select your server then **Next**.
4. In the Select Server Roles window, expand the **Web Server (IIS)** role.
5. Expand **Web Server**
 - a. Under **Common HTTP features** select:
 - **Default Document**
 - **Directory Browsing**
 - **HTTP Errors**
 - **Static Content**
 - b. Under **Application Development** select the following:
 - **.NET Extensibility 4.5**
 - **ISAPI Extensions**
 - **ISAPI Filters**
 - c. To speed up file transfer over the network, we recommend enabling compression: Under **Performance** select **Static Content Compression** and **Dynamic Content Compression**.
 - d. Under **Health and Diagnostics** select:
 - **HTTP Logging**
 - **Request Monitor**
6. Under **Management Tools** select:
 - **IIS Management Console**
7. Select **Next** then **Install**.

Configuring IIS applicationHost.Config

This part describes which actions should be taken to change the `applicationHost.Config` to allow the definition of website-specific settings in the `Web.config` file for Content Manager websites and to set the necessary mimetype definitions for compression.

Before you begin

The steps for configuring IIS web services must have been executed, especially the static and dynamic compression feature for IIS needs to be installed.

About this task

The `ApplicationHost.config` file can be found in the folder `%WINDIR%\system32\inetsrv\config`. It is the root file of the configuration system when you are using IIS 7 and above. It includes definitions of all sites, applications, virtual directories and application pools, as well as global defaults for the web server settings. It has definitions for locking-down most IIS sections to the global level, so that by default they cannot be overridden by lower-level `Web.config` files in the hierarchy. To make configuration easier, we will unlock some of these global level settings, so we can define these settings in the `Web.config` file for Content Manager websites.

Procedure

1. Make the necessary changes to allow the definition of website specific settings in the `Web.config` file for the website.
 - a. Start `cmd.exe` as Administrator.
 - b. Execute the following statements in the cmd window:

```
%windir%\system32\inetsrv\appcmd unlock config /section:system.webServer/serverRuntime /commit:apphost
%windir%\system32\inetsrv\appcmd unlock config /section:system.webServer/defaultDocument /commit:apphost
%windir%\system32\inetsrv\appcmd unlock config /section:system.webServer/staticContent /commit:apphost
%windir%\system32\inetsrv\appcmd unlock config /section:system.webServer/directoryBrowse /commit:apphost
%windir%\system32\inetsrv\appcmd unlock config /section:system.webServer/handlers /commit:apphost
%windir%\system32\inetsrv\appcmd unlock config /section:system.webServer/urlCompression /commit:apphost
```

2. Set the necessary mimetype definitions for static compression:
 - a. Start 64-bit PowerShell as Administrator.
 - b. Execute the following statements in the PowerShell window:

```
Set-ExecutionPolicy Unrestricted -Force
$is64bit = [Environment]::Is64BitProcess
if (!$is64bit) {
    throw "This script requires a 64-bit Powershell session"
}
Import-Module WebAdministration
# Define the mimetypes for IIS that can be statically compressed
$staticcompression = @(
    @{mimeType='text/*'; enabled='True'},
    @{mimeType='message/*'; enabled='True'},
    @{mimeType='application/x-javascript'; enabled='True'},
```

```

    @{mimeType='application/atom+xml'; enabled='True'},
    @{mimeType='application/xaml+xml'; enabled='True'},
    @{mimeType='application/octet-stream'; enabled='True'},
    @{mimeType='application/javascript'; enabled='True'},
    @{mimeType='*/*'; enabled='False'}
  )
  # Set the specified static mimetypes in the compression settings
  # in applicationHost.config
  $filter = 'system.webServer/httpCompression/statictypes'
  Set-Webconfiguration -Filter $filter -Value $staticcompression

```

3. Set the necessary mimetype definitions for dynamic compression:
 - a. Start 64-bit PowerShell as Administrator.
 - b. Execute the following statements in the PowerShell window:

```

Set-ExecutionPolicy Unrestricted -Force
$Is64bit = [Environment]::Is64BitProcess
if (!$Is64bit) {
    throw "This script requires a 64-bit Powershell session"
}
Import-Module WebAdministration
# Define the mimetypes for IIS that can be dynamically compressed
$dynamiccompression = @(
    @{mimeType='text/*'; enabled='True'},
    @{mimeType='message/*'; enabled='True'},
    @{mimeType='application/x-javascript'; enabled='True'},
    @{mimeType='application/soap+xml'; enabled='True'},
    @{mimeType='application/xml'; enabled='True'},
    @{mimeType='application/json'; enabled='True'},
    @{mimeType='application/octet-stream'; enabled='True'},
    @{mimeType='application/javascript'; enabled='True'},
    @{mimeType='*/*'; enabled='False'}
)
# Set the specified dynamic mimetypes in the compression settings
# in applicationHost.config
$filter = 'system.webServer/httpCompression/dynamictypes'
Set-Webconfiguration -Filter $filter -Value $dynamiccompression
# Note that compression can be set per web.config file

```

- c. Close PowerShell.

Prerequisites for Java

The Java tools tested with this version of Content Manager can be retrieved online from Content Manager upon request.

The compatible Java versions are specified in the Content Manager software requirements.

The following Content Manager components use Java:

- DITA Open Toolkit (publishing engine).
- TrisoftSolrLucene (search engine).

Starting from JDK 11, we refer to OpenJDK as the alternative for JDK and JRE.

Note: If you install JDK 64 bit, by default the 64 bit JRE is installed.

Prerequisites for publishing engine

These software packages are required on the server that handles Content Manager publishing.

Java Help

Only required if you use the Content Manager Publishing engine to generate Java Help files.

Qualified version(s):

The suggested installation path is `c:\JavaHelp` which results in the availability of the following: `c:\JavaHelp\jh<version>\src.jar` Content Manager

Where `<version>` is the version of Java Help.

InstallTool input parameters allow you to indicate the path before installation using the variable **ps_javahelp_home**.

The javahelp-`<version>`.zip file tested with this release of Content Manager can be retrieved online from SDL upon request.

- extract the contents of the zip file
- create the `c:\JavaHelp\` folder
- copy or move the extracted `jh<version>` folder into the `c:\JavaHelp\` folder

HTML Help Workshop

Only required for the Content Manager Publishing engine.

A `htmlhelp.zip` package can be retrieved online from SDL upon request. That package contains a tested version of HTML Help Workshop.

Extract the executable in `c:\Program Files (x86)\HTML Help Workshop`.

Antenna House XSL Formatter

Required if you use the Content Manager Publishing engine and the Antenna House XSL Formatter software by Antenna House to render your output.

To allow the proper rendering of non-Western language such as Thai or the East Asian languages, you must have the specialized fonts available. Content Manager expects that all available complex script, right-to-left and East Asian language support are available.

Content Manager is tested with the currently supported Antenna House XSL Formatter (specified in the *Software requirements* list) which can be retrieved online from SDL upon request.

Note: You may use a later version of Antenna House XSL Formatter; check with your SDL customer support representative if you have any questions.

Content Manager pre-installation checklist

Use this checklist to make sure that all the necessary pre-installation actions have been properly carried out before installing Content Manager.

Refer to the hardware and software requirements list to ensure that the correct versions are installed before you install Content Manager.

Layer	Type	Requirement	Completed?
Database	Hardware	Check hardware requirements for the database server.	
Database	Software	Check that the version of the database system is supported for this release, including the exact service pack.	
Database	Software	Make sure the Microsoft SQL Server installation is AccentSensitive , CaseInsensitive and Unicode-ready .	
Application/Web	Hardware	Check hardware requirements for the application server.	
Application/Web	Environment	The designated database user (<i>isource</i>) has the required system administrator rights.	
Application/Web	Environment	The designated app/web user (InfoShare) has the correct regional options set (dd/MM/yyyy).	
Application/Web	Environment	Make sure you do not forcefully unload the user registry as user logoff is enabled (Windows application server).	
Application/Web	Software	Check that a valid security certificate is available for the web server application (HTTPS enabling).	
Application/Web	Software	Check that the version of the application system is supported for this release, including the exact service pack.	
Application/Web	Software	Check that IIS web services are installed.	
Application/Web	Software	Make sure that a supported version of Microsoft .NET Framework is installed.	
Application/Web	Software	Make sure that a supported version of Microsoft .NET is installed.	

Layer	Type	Requirement	Completed?
Application/Web	Software	If Oracle is used as RDBMs, make sure that the Oracle Client Configuration is configured.	
Application/Web	Software	If publishing to JAVA help files is chosen, check that a supported version of Java Help is installed.	
Application/Web	Software	Check that a supported version of Java is installed.	
Application/Web	Software	If publishing to CHM files is chosen, check that a supported version of HTML Help Workshop is installed.	
Application/Web	Software	If publishing to PDF files is chosen, check that a XSL-FO renderer such as Antenna XSL Formatter is installed.	

Creating Content Manager databases

Before you install the Content Manager application server, you must create the core Content Manager database, as well as a number of additional databases that are required for specific features.

The Content Manager databases can reside on either a Microsoft SQL Server or Oracle database server. Your database server must be installed with the approved version of database software before beginning with these procedures.

Note: An Oracle setup is more complex than a Microsoft SQL Server setup. This is because the Microsoft SQL Server installation and configuration is explained using a Windows user interface. If you have the choice and are not an Oracle DBA, we advise that you install on a Microsoft SQL Server platform.

Setting up the Content Manager database on Microsoft SQL Server

Setting up the Content Manager database on Microsoft SQL Server requires configuration of the server and creation of the database.

Configuring Microsoft SQL Server

The database setup is done on the Microsoft SQL server.

First read the pre-installation notes for SQL Server provided in this documentation.

The SQL Server installation has to be an **AccentSensitive, CaseInsensitive, Unicode-ready** installation.

- If you are performing a fresh SQL Server installation, make sure that in the **Database engine Collation** settings, **Accent-sensitive** is selected and Case-sensitive is not selected.
- The typical Content Manager collation is **SQL_Latin1_General_CP1_CI_AS** (not the often mistaken collation Latin1_General_CI_AS). Depending on the SQL Server version, the collation **SQL_Latin1_General_CP1_CI_AS** is also displayed as **Dictionary order, caseinsensitive, for use with 1252 Character Set**.
- You can check the collation name by issuing a query in **SQL Server Management Studio** connected to your server.
 - Select **New Query** then enter `select ServerProperty('Collation')`.
 - Select **Execute**.
 - Verify that the result shows an Accent-sensitive (AS), Case-insensitive (CI) collation name.
For more information refer to Collations in the SQL Server help files.

We recommend authentication based on named SQL Server login ID and on Windows accounts.

- Check or modify authentication in **SQL Server Management Studio**, right-click **ServerName**, then click **Properties** and select **Security** on the left pane.
- In the **Server authentication** pane on the right, select **SQL Server and Windows Authentication Mode**.

SQL Server Agent is part of the SQL Server software.

- Check that this Windows Service is set to automatically start upon server reboot. In the **Control Panel** select **System and Security** then **Administrative Tools** then open **Services**.
- Verify that **SQL Server Agent** startup type is **Automatic**.

Creating a Microsoft SQL Server database for Content Manager

Create a database for the Content Manager data collection.

Procedure

1. Open **SQL Server Management Studio**.
2. Right-click on **Databases** then click **New Database...**
3. Enter a database name (e.g. `ContentManager`).
4. Click **Options** in the left pane.
5. In the **Collation** field, select: **SQL_Latin1_General_CP1_CI_AS**.
6. Select the appropriate **Recovery model**.
 - **Full**: All transactions are logged. The recommended choice for production databases.
 - **Simple**: A portion of the transactions are logged. A choice for some test or development databases.
 - **Bulk-Logged**: temporary setting used for specific large-scale bulk operations.

Note: The recovery model determines the number of transactions logged for later system recovery. Whereas a **Full** model provides the best security with a higher points-in-time for recovery, in some situations a **Full** model may cause logs to grow beyond system's ability to process them. Check your database documentation for more information.

7. In the **Compatibility** level field, select option corresponding to the version of SQL Server you are using.
8. Click **OK**.

Importing data from the SQL dumpfile

Import the sample Content Manager database dump to validate the configuration and for training purposes.

About this task

The backup data you import can come from the same version of SQL server or from a previous version.

Procedure

1. In the SQL Server Management Studio window, under **Databases**, right-click on the database you created.
2. Click **Tasks > Restore > Database**.
3. In the **General** tab of the Restore Database window, select that you want to restore from a **Device**.
 - a. Click the ellipsis button next to the **Device** field.
 - b. Click **Add** in the resulting Specify Backup window.
 - c. Locate and select the latest available dump provided on the installation CD in a subfolder of the `\Database\Dump\` folder.
 - d. Click **OK**.
 - e. The **Database** field under **Source** is populated with the name of the database in the backup file.

- f. In the **Database** field under **Destination**, select the name of the database you created (e.g. `ContentManager`). This is the database that is to be populated with the data from the backup/dump file.

Note: Make sure to select this after selecting the source otherwise it can default to another database name.

4. In the **Files** tab of the **Restore Database** Window:
 - a. For the **Rows Data** select the data file path of the database you created (e.g. `C:\Program Files\Microsoft SQL Server\MSSQL14.SQL2017\MSSQL\DATA\ContentManager.mdf`).
 - b. For the **Log** select the log file path of the database you created (e.g. `C:\Program Files\Microsoft SQL Server\MSSQL14.SQL2017\MSSQL\DATA\ContentManager_log.ldf`).
5. Under the **Options** tab, select **Overwrite the existing database**.
6. Click **OK**. The database is restored.
7. After restoring the database, use **SQL Server Management Studio** to:
 - a. Open the **Properties** window,
 - b. Go to the **Files** tab,
 - c. Check and adapt (if necessary) the logical name.

File type	Logical Name
Rows Data	Set Logical Name to <dbname> (e.g. <code>ContentManager</code>)
Log	Set Logical Name to <dbname>_Log (e.g. <code>ContentManager_Log</code>)

- d. Check the recovery model and verify that **Full** is selected for the **Recovery model**.

Removing the database user and schema

To ensure successful creation of a new database user and schema, delete the user that was created when importing the sample data, as well as the schema of the same name if one exists.

About this task

A database user in SQL Server exists on two levels, as an account on the SQL Server level and as an account on your database. Depending on the kind of initial database setup dump you received, you could have problems creating your new database user. Therefore, you should delete the Content Manager database designated user (by default named `isource`) and schema if one is present.

Note: The user listed within the created database part is to be removed and not the general SQL Server part listed under Security > Logins.

Procedure

1. In the SQL Server Management Studio window, locate and open the tree under the newly created database.
2. Open **Security > Schemas**.
3. Right-click on **isource** if it appears in the list, then click **Delete**.
A Delete Object window displays.

Note: The **isource** user may not exist under **Schemas**. If it does not exist, skip this and the next step; continue to the step to open **Security > Users**.

4. Click **OK** to confirm the removal.
5. Open **Security > Users**.
6. Right-click on **isource** then click **Delete**.
A Delete Object window displays.
7. Click **OK** to confirm the removal.

Creating a new database user and schema

Add a new user to connect to the newly created database.

Procedure

1. On the database server, open the **SQL Server Management Studio**.
2. In the left pane under the server name open **Security**.
3. Right-click on **Logins** then select **New Login...**
A Login - New window displays.
4. In the **Login name** field, enter an user name (e.g. isource).
5. **SQL Server Authentication** should be selected. Enter a **Password** (e.g. isource) and **Confirm password** for SQL Server Authentication.

Note: SDL is not able to assist you if you do not know the password so it is advised to store the password in a secure place.

6. Depending on your local password policy, you can enforce password policy and password expiration.

Note: Keep in mind to change the connect string whenever you change the password of the database user!

7. Use the drop down list to select the **Default database**; select your newly created database.
No other changes are required for the General information.
8. Click **Server Roles** in the left pane.
9. Select (check the boxes next to) **public** and **sysadmin** in the right pane.

This allows the Content Manager DBUpgradeTool (DBUT) to fully execute all necessary tasks to update your database with new releases.

Notice: If you want to reduce the server roles for everyday work, read “Optionally minimize the database user's roles and permissions” on page 53.

10. Click **User Mapping** in the left pane.
11. Select (check the boxes next to) the newly created database in the upper right pane.
12. In the upper right pane, in the **Default Schema** field for your database, enter **dbo**.
13. In the bottom pane, select (check the boxes next to) **db_owner** and **public**.

Notice: If you want to reduce the permissions for day to day usage, read “Optionally minimize the database user's roles and permissions” on page 53.

14. In the Login - New window, click **Status** in the left pane.
15. Verify that **Grant** is selected for **Permission to connect to the database engine** and that **Enabled** is selected for **Login**.
16. Click **OK**.
17. Click **File > Exit**.

Optionally minimize the database user's roles and permissions

Describes how to optionally reduce the roles and permissions of the database user for everyday usage.

About this task

Optional execution to minimize the permissions for normal operations outside of the upgrade time frame.

Note: The following steps must be executed by a user who is administrator on the database server.

Procedure

1. On the database server, open **SQL Server Management Studio**.
2. In the left pane under the server name, open **Security > Logins**.
3. Right-click the database user (e.g **isource**) and select **Properties**.
4. Revoke the server role **sysadmin**.

The server role **sysadmin** provides the ability to perform any activity on the server. Content Manager DBUpgradeTool (DBUT) requires this server role to create the standard database job and add extra (error) messages, for example. In order to allow DBUT to fully execute all necessary tasks during an upgrade, we advice to reinstate the **sysadmin** server role for the duration of that task. However, during everyday usage you can revoke **sysadmin** using the following steps:

- a. Select **Server Roles** in the left pane.
- b. Deselect **sysadmin** in the right pane. Make sure that **public** is still selected.
5. Revoke database role **db_owner**.

Note: Revoking the database role **db_owner** should be done only after revoking the server role **sysadmin**.

- a. Select **User Mapping** in the left pane.
- b. Select the correct database in the upper right pane.
- c. In the bottom pane, un-check the box next to **db_owner**. Make sure that **public** is still selected.
6. Select **OK**.
7. After revoking the database role **db_owner**, add the minimal required permissions.

In order for the Content Manager application to work without issues, the database user needs the following permissions:

Name	Description	Usage
SELECT	Retrieve information/ records from the database	Everywhere
INSERT	Insert new records into the database	Everywhere
UPDATE	Update records in the database	Everywhere
DELETE	Delete records from the database	Everywhere
EXECUTE	Execute a stored procedure in the database	<p>Stored procedures are used everywhere to:</p> <ul style="list-style-type: none"> • Create new objects (maps, topics, publications, users, LOV values...) and get the newly created IDentity back. • Delete objects • Cleanup left-overs during a nightly maintenance job • ...
CREATE TABLE	Create a new table	<p>DBUpgradeTool: during the upgrade of the database from one version to another version, we might introduce new tables.</p> <p>Full-text search: out-of-the-box the tables for the full-text search are created when you start the Crawler for that installation for the first time.</p>
CREATE VIEW	Create a new view	DBUpgradeTool: during the upgrade of the database from one version to another version, we are dropping and recreating views.

Name	Description	Usage
CREATE FUNCTION	Create a new function	DBUpgradeTool: during the upgrade of the database from one version to another version, we are dropping and recreating functions.
CREATE PROCEDURE	Create a new stored procedure	DBUpgradeTool: During the upgrade of the database from one version to another version, we are dropping and recreating stored procedures.
REFERENCES	Create foreign keys between two tables	DBUpgradeTool: During the upgrade of the database from one version to another version, we might introduce new tables and add new foreign keys between those new tables and the existing tables. Full-text search: out-of-the-box the tables for the full-text search are created when you start the Crawler for that installation for the first time, and we are also adding new foreign keys between those new tables and the existing tables.
ALTER ANY SCHEMA	Create, alter and delete objects in any schema	DBUpgradeTool: during the upgrade of the database from one version to another version, we are creating/altering/deleting tables, views, functions, stored procedures... in the schema <code>dbo</code> . Full-text search: we need to create the tables in the schema <code>dbo</code> for the full-text search.

You can grant the necessary permissions to the database user using the following steps:

- In **SQL Server Management Studio** open the following file:
`C:\InfoShare\AppPROJECTSUFFIX\Database\InfoShareCM\Common\SQLServer\Tools\GrantPermissionsToDBUser.sql`
 where *PROJECTSUFFIX* is a suffix string.
- If your database user is not `isource`, change `isource` to the correct database user.
- Run the script as an administrator.
- Connect with the database user (e.g. `isource`) and run the following query to check that the database user has the required permissions.

```
SELECT * FROM fn_my_permissions(null, 'DATABASE')
```

Setting up the Content Manager database for Oracle

The installation makes use of the Oracle Database Configuration Assistant (DBCA) and command line programs to create and set up the database. This allows for anyone with a mixture of Windows and UNIX knowledge to be able to set up an environment on any Oracle hosting machine.

The configuration instructions refer to a Windows environment when noting system variables and file paths.

These instructions guide a knowledgeable person through the configuration so that no important steps are forgotten. However, it does not provide all explanations, or options pertaining to each step.

Note: The default database name is **ISH**.

Note: In case of issue, be sure to check the troubleshooting section dedicated to the database installation.

Configuring Oracle

Before creating your database, some configuration tasks are required.

Oracle database configuration requirements

The users who can configure Oracle must have permissions and access as required and be familiar with Oracle and Microsoft environments.

The provided configuration instructions are written for administrators who have knowledge of the Oracle and Microsoft environments.

Make sure that you satisfy the following requirements before you begin:

- Having a DBA role is required for a database migration.
- Reboot after Oracle installation for making sure that all Oracle environment settings are available to you.

Also note:

- All executed actions should be done in the same command window for making sure that shell specific settings, such as `ORACLE_SID` or `ORACLE_HOME`, are available.
- All paths are examples only. Paths are system specific, so make sure that all file paths are valid and contain the correct file(s), and beware of read-only flags on files.
- The default database name is **ISH** and is used in examples in the procedures.

Activating the Listener service for Oracle

You must start the Oracle listener service so that incoming client connection requests are received and sent to the database server.

About this task

Activate the Listener service for Oracle in one of two ways:

- If a general listener is available, select it,
- Otherwise, create a specific listener for your database and activate it, following the steps below.

Procedure

1. Start the Net Configuration Assistant. This Assistant is provided by Oracle.
2. Select **Listener Configuration** in the window that opens, then select **Next**.
3. Select **Add** in the following window, then select **Next**.
4. Enter a name for the new listener, then select **Next**.
5. Select **TCP** as the selected protocol in the list, then select **Next**.
6. Select **Use the standard port of 1521** in the following window, then select **Next**, or specify a custom port if using.
7. Complete the creation process by selecting **Next** again.

Creating the Oracle database for the Content Manager Repository

Use the Database Configuration Assistant to create the Oracle database for the Content Manager Repository, using a template.

Before you begin

To perform this task, you must be a member of the local Windows administration group, as well as of the `ORA_DBA` group.

About this task

To prepare your environment for the Oracle configuration, first copy the template file to your server. The version mentioned below has been quality-tested with this version of Content Manager.

Target directory on the server: `ORACLEHOME\assistants\dbca\templates\`

Procedure

1. Go to the folder `C:\InfoShare\App\Database\InfoShareCM\Common\Oracle\Oracle193.Admin\`.
2. Copy the template `SDL-Trisoft.InfoShare-Database-Template.dbt` to a location of your choosing, for example, `ORACLEHOME\assistants\dbca\templates`, where `ORACLEHOME` is the Oracle home directory on the server.
3. Start the Database Configuration Assistant (DCA). This Assistant is provided by Oracle.
4. On the **Database Operation** page, select **Create Database**, then select **Next**.
5. Change the configuration mode to **Advanced configuration**, then select **Next**.
6. On the **Database Template** page, select `SDL Trisoft InfoShare Database Template (19)`, then select **Next**.
7. On the **Database Identification** page, fill in the **Global Database Name** field with the

database name; make sure that the **Create as Container Database** option is *not* selected, and then select **Next**.

8. On the **Storage Option** page, do the following:
 - a. Select **Use following for the database storage attributes**.
 - b. In the **Database files storage types** list, select **File System**.
 - c. Fill in the **Database files location** field with the path to the database.
 - d. Select **Next**.
9. Leave the **Fast Recovery Option** page as is, then select **Next**.
10. On the **Network Configuration** page, select the Listener that you previously selected or created for this database, then select **Next**.
11. Leave the **Database Options** page as is and select **Next**.
12. On the **Configuration Options** page, on the **Memory** tab, select **Use Automatic Shared Memory Management**. You may want to adapt the values to your specific needs.
13. On the **Configuration Options** page, on the **Sizing** tab, you may want to increase the processes value, depending on the size of your system. Each current database consumer (end users, services, background tasks...) uses a process, so you need to set a sufficient amount of them if you want all the consumers to be able to use the database in parallel.
14. Leave the rest of the **Configuration Options** page as is and select **Next**.
15. On the **Management Options** page, make sure that the specified port is unique and select **Next**.
16. On the **User Credentials** page, fill in the password fields, then select **Next**.
17. On the **Creation Option** page, select **Create database**, then select **Next**.
18. On the **Summary** page, select **Finish**.

Creating the designated **ISOURCE** database user

You must create the **ISOURCE** designated database user for the new database.

Procedure

1. If the folder `c:\oracle\admin\ISH\create\` on the server does not exist, create it now.
2. Copy `PACKAGEROOT\Database\InfoshareCM\Common\Oracle\Create\isrcuser.i` (where `PACKAGEROOT` is the root folder of the installation package) to the folder `c:\oracle\admin\ISH\create\`, and make sure the file is writable.
3. Check the paths, commands, usernames and passwords in the file. The examples in the file are Windows-specific. Open the file in a plain-text editor and change the example values as needed, especially the username and password of the designated user, to match your environment.
4. Open a command shell for your operating system.
5. On the command prompt, define the following environment variables, with the following values:

Environmet variable	Value
ORACLE_SID	ISH
ORACLE_HOME	the full path of the location where you copied the application

- Start SQLPlus by entering the following on the command prompt: `sqlplus SYS AS SYSDBA`
- Enter the following commands from the same command prompt:

```
SPOOL C:\oracle\admin\ISH\create\dbadmin2.log
CONNECT SYS/CHANGE_ON_INSTALL AS SYSDBA
@C:\oracle\admin\ISH\create\isrcuser.i
CONNECT ISOURCE/isource
@?/RDBMS/ADMIN/catdbsyn.sql
SPOOL OFF;
```

Note: If you receive the error "SP2-0606: Cannot create SPOOL file c:\oracle\admin\ISH\create\dbadmin2.log", then you have no folder c:\oracle\admin\ISH\create\.

Importing the data with Oracle

You can import sample data in order to validate your configuration or for training purposes. Use the Data Pump Import tool for this.

Procedure

- If the folder `c:\oracle\admin\ISH\dpdump\` does not exist on the server, create it now.
- Copy `PACKAGEROOT\Database\InfoShareCM\Common\Oracle\impdp\impdp.par` (where `PACKAGEROOT` is the root folder of your package) to the folder `c:\oracle\admin\ISH\dpdump\`, and make sure the file is writable.
- Check the paths, commands, usernames and passwords in the file. The examples in the file are Windows-specific. Open the file in a plain-text editor and change the example values as needed, especially the name of the export file (`DUMPFIL` parameter) and the designated schema owner (`SCHEMAS` parameter), to match your environment.
- Open a command shell for your operating system.
- On the command prompt, define the following environment variables, with the following values:

Environmet variable	Value
ORACLE_SID	ISH
ORACLE_HOME	the full path of the location where you copied the application

- Start SQLPlus by entering the following on the command prompt: `sqlplus SYS AS SYSDBA`
- Make sure the `ISOURCE` user has read and write access to the folder:

```
GRANT read, write ON DIRECTORY data_pump_dir TO isource;
```

8. Make sure the file from the Data Pump Export is copied to the DATA_PUMP_DIR:

```
SELECT directory_path FROM dba_directories WHERE directory_name =  
'DATA_PUMP_DIR';
```

9. Exit SQLPlus, so you are back at the command prompt.
10. Perform the import by executing the following command:

```
impdp isource parfile="C:\oracle\admin\ISH\dpdump\impdp.par"
```

Disabling optimizer dynamic sampling

Dynamic sampling is a functionality that gathers statistics on the fly during query execution. When switched on, it can adversely affect performance. For that reason, you should ensure that the `sys` user disables optimizer dynamic sampling in the Oracle database.

Procedure

1. Open a command shell for your operating system.
2. Start SQLPlus by entering the following on the command prompt: `sqlplus SYS AS SYSDBA`
3. Enter the following command:

```
ALTER SYSTEM SET optimizer_dynamic_sampling=0
```

Validating the Oracle database

The newly imported Oracle database needs some packages, triggers and more to be (re-)compiled for the database to be valid.

Before you begin

To perform this task, the `ORACLE_SID` and `ORACLE_HOME` environment variables must be set correctly (this is normally done during the `ISOURCE` user creation).

Procedure

1. From a command shell in which where the `ORACLE_SID` and `ORACLE_HOME` environment variables are set correctly, enter the following from the command prompt:

```
SQLPLUS /NOLOG
```

2. Enter the commands to validate the database. Do not use a script file.

```
CONNECT SYS/CHANGE_ON_INSTALL AS SYSDBA
@?/rdbms/admin/utlrp;
```

All objects in the database should be valid.

Editing `tnsnames.ora` for an Oracle database

For Oracle databases, the `tnsnames.ora` file defines the information for a connection to the database server and to the database instance for the Content Manager repository. Modify the file on the Oracle database server, and on all systems that communicate with the Oracle database server.

About this task

If the Oracle database server and client software are installed on the same system, you must edit the `tnsnames.ora` file under each Oracle home directory.

Procedure

1. Sign in to the server as an administrator user.
2. Go to the folder `ORACLEHOME\network\admin\`, where `ORACLEHOME` is the Oracle home directory.
3. If this folder does not yet contain a file called `tnsnames.ora`, create an empty plain-text document and save it as `tnsnames.ora` in this folder.
4. Open `ORACLEHOME\network\admin\tnsnames.ora` in a plain-text editor.
5. Add the following to the file. Make sure that the first line starts on position 1, that is, that it contains no leading whitespace.

```
NETSERVICENAME =
(DESCRIPTION =
  (ADDRESS_LIST =
    (ADDRESS = (PROTOCOL = TCP)
      (HOST = HOSTNAME)
      (PORT = 1521))
  )
(CONNECT_DATA =
  (SERVICE_NAME = SERVICENAME)
)
)
```

where:

- `NETSERVICENAME` is an alias, for example, `ISH.WORLD`, that is used for a connect descriptor.
- `HOSTNAME` is the IP address or name of the database server, for example, `devserver01` or `127.0.0.1`.
- `SERVICENAME` is a combination of the `db_name` and `db_domain` values in the `C:\oracle\admin\ISH\pfile\PFIL\initISH.ora` file. For example:

```
SERVICE_NAME = ISH.ORASERVER.DOMAIN.NAME
```

where `ISH` is the `db_name` value and `ORASERVER.DOMAIN.NAME` is the `db_domain` value in the `initISH.ora` file.

6. Save and close the file.

Analyzing the Oracle database

After the import, run a script that creates statistics used by the queries.

Before you begin

ORACLE_SID and ORACLE_HOME variables are set correctly (this is normally done during the ISOURCE user creation).

Procedure

1. At a command prompt where the environment variables ORACLE_SID and ORACLE_HOME are set correctly (this is normally done during the ISOURCE user creation), enter the following commands:

```
SQLPLUS /NOLOG  
CONNECT ISOURCE/isource
```

2. Run the `PACKAGEROOT\Database\InfoshareCM\Common\Oracle\Tools\FullAnalyze.sql` script, where `PACKAGEROOT` is the root folder of your installation package.

Creating databases for Content Manager security

To implement security for Content Manager clients, you need to create three additional databases.

Databases

The following table describes the databases and their functions:

Feature	Description
Tridion Access Management	Tridion Access Management (or simply Access Management) provides implementors with a simplified approach to identity management and gives administrators a central location for ongoing management of access to applications.
Backend for frontend	<i>Backend for Frontend</i> , or BFF, refers to an architectural pattern that uses a middle layer between the frontend clients and the backend. BFF also refers to the layer itself and each client has a dedicated BFF. A single BFF database is used for the various BFFs.
Tridion Docs Identity Provider	

Database server requirements

The Content Manager databases can reside on either an Microsoft SQL Server or Oracle database server. Your database server must be installed with the approved version of database software before beginning with these procedures.

Note: An Oracle setup is more complex than a Microsoft SQL Server setup. If you have the choice and are not an Oracle DBA, we advise that you install on a Microsoft SQL Server platform.

To complete this task, you need access to a database server machine that runs a supported database version. Database support is the same as for Content Manager.

PowerShell script requirements

To create these databases, you run PowerShell database scripts, which require a machine that meets the following requirements:

PowerShell

You require Microsoft Windows PowerShell 5.1. You can download Microsoft Windows Management Framework 5.1, which includes Microsoft Windows PowerShell 5.1, from this location: <http://aka.ms/wmf5download>

Operating system

You require an operating system that supports both the required PowerShell software and any software for the database you intend to install. As a general rule, ensure that the latest (security) updates are installed on your operating system.

Database client software

For Oracle databases, you require both of the following:

- Oracle Services for Microsoft Transaction Server (ORAMTS)
- Oracle Data Provider for .NET (ODP.NET)

For maintenance, configuration and debugging purposes, RWS recommends that you also install the Oracle SQL Developer PL/SQL IDE (or SQL*Plus) and Oracle Net.

Environment variables

For Oracle databases where you have defined a Net Service Name for each database in a `tnsnames.ora` file, you must also have defined a `TNS_ADMIN` environment variable. Set it to the directory where `tnsnames.ora` resides.

Microsoft .NET Framework

You require a .NET Framework version. The one to use depends on your Windows Server operating system version:

- If you run Microsoft Windows Server 2022, you can use Microsoft .NET Framework 4.8.1. You can download Microsoft .NET Framework 4.8.1 from the following location: <https://dotnet.microsoft.com/en-us/download/dotnet-framework/net481>
- If you run Microsoft Windows Server 2019 x64, you must use Microsoft .NET Framework 4.8. You can download Microsoft .NET Framework 4.8 from the following location: <https://dotnet.microsoft.com/en-us/download/dotnet-framework/net48>

Security

You need to be logged in as a user with sufficient security clearance. For example, to run a script that installs a database, you must be logged in as a user with rights to create that database.

Creating a database system administrator user for Oracle

Tridion Docs ships with an SQL script that creates a database system administrator user. After running the script, you can use this new user when you run a PowerShell script to create a database for Content Manager security. The privileges and roles created for this user are the minimum requirements for database installation.

Procedure

1. On your Tridion Docs installation media, go to the folder `Database\Shared\Scripts\Oracle\Create\`.
2. Run the SQL script `TridionSYSUser.sql` (say, from SQL*Plus).
3. When prompted, give the following information:

Username	The name of the database system administrator user that can create the databases. RWS proposes the user name <code>TRIDION_DOCS_SYS</code> .
	Note: You cannot use a user that must connect as <code>SYSOPER</code> or <code>SYSDBA</code> with the PowerShell script.
Password	The password of this user
Default tablespace	The default tablespace for objects the user creates
Temporary tablespace	The tablespace for the user's temporary segments

What to do next

Once this user has been created, you can proceed to create your databases for Content Manager security.

Creating the Access Management database

Create the Access Management database using the provided PowerShell script.

Before you begin

- To complete this task, you need access to a database server machine that runs a supported database version. Database support is the same as for Content Manager.

About this task

Procedure

1. On your database server machine, open a PowerShell prompt.
2. For Oracle databases, specify a host, port, service name and other connection information for the PowerShell script, either *before* or *while* running the script:
 - *Before* you run the script, you can define a variable in PowerShell, let's say `$MyDatabaseServer`, and set it to your connection string. When you invoke the script, you then append the string `-DatabaseServer $MyDatabaseServer` to the PowerShell command.
 - Alternatively, you can just invoke the script as is, and *while* you run the script, PowerShell prompts you for a value for **Net Service**, and you can then enter one of the following:
 - Enter the Net Service Name for this database if you have defined a Net Service Name in a `tnsnames.ora` file and specified the location of that file in a `TNS_ADMIN` environment variable.
 - Enter the string `%manual%` to let the script prompt you for the following: **Host name**, **Port** and **Service name**.
 - Enter the actual connection string directly on a single line if you have more to provide than just a host, port and service name. For example:

```
(DESCRIPTION = (ADDRESS = (PROTOCOL = TCP) (HOST = myhost) (PORT = 1521)) (CONNECT_DATA = (SERVICE_NAME = ora)))
```

3. Run the following PowerShell command, following the instructions that appear:

```
& '.\Install Access Management database.ps1'
```

By completing this step, you have created the Access Management database.

Creating the Tridion Docs Identity Provider database

Create the database for Tridion Docs Identity Provider using the provided PowerShell script.

Before you begin

- To complete this task, you need access to a database server machine that runs a supported database version. Database support is the same as for Content Manager.
- To run PowerShell database scripts for this database, the machine must meet the requirements described in "Creating databases for Content Manager security" on page 62.

Procedure

1. On your database server machine, open a PowerShell prompt.
2. In the location of your Tridion Docs installation media, navigate to the folder for the type of database you are creating:
 - For a Microsoft SQL Server database: `Database\ InfoShareID\ SQLServer\`
 - For an Oracle database: `Database\ InfoShareID\ Oracle\`
3. For Oracle databases, specify a host, port, service name and other connection information for the PowerShell script, either *before* or *while* running the script:
 - *Before* you run the script, you can define a variable in PowerShell, let's say `$MyDatabaseServer`, and set it to your connection string. When you invoke the script, you then append the string `-DatabaseServer $MyDatabaseServer` to the PowerShell command.
 - Alternatively, you can just invoke the script as is, and *while* you run the script, PowerShell prompts you for a value for **Net Service**, and you can then enter one of the following:
 - Enter the Net Service Name for this database if you have defined a Net Service Name in a `tnsnames.ora` file and specified the location of that file in a `TNS_ADMIN` environment variable.
 - Enter the string `%manual%` to let the script prompt you for the following: **Host name**, **Port** and **Service name**.
 - Enter the actual connection string directly on a single line if you have more to provide than just a host, port and service name. For example:

```
(DESCRIPTION = (ADDRESS = (PROTOCOL = TCP) (HOST = myhost) (PORT = 1521)) (CONNECT_DATA = (SERVICE_NAME = ora)))
```

4. Run the following PowerShell command, following the instructions that appear:

```
& '.\Install Infoshare Identity Provider database.ps1'
```

By completing this step, you have created the `InfoShareID` database.

Creating the Backend for Frontend database

Create the Backend for Frontend (BFF) database using the provided PowerShell script.

Before you begin

- To complete this task, you need access to a database server machine that runs a supported database version. Database support is the same as for Content Manager.
- To run PowerShell database scripts for this database, the machine must meet the requirements described in "Creating databases for Content Manager security" on page 62.

About this task

Backend for Frontend, or BFF, refers to an architectural pattern that uses a middle layer between the frontend clients and the backend. BFF also refers to the layer itself and each client has a dedicated BFF. A single BFF database is used for the various BFFs.

Procedure

1. On your database server machine, open a PowerShell prompt.
2. For Oracle databases, specify a host, port, service name and other connection information for the PowerShell script, either *before* or *while* running the script:
 - *Before* you run the script, you can define a variable in PowerShell, let's say `$MyDatabaseServer`, and set it to your connection string. When you invoke the script, you then append the string `-DatabaseServer $MyDatabaseServer` to the PowerShell command.
 - Alternatively, you can just invoke the script as is, and *while* you run the script, PowerShell prompts you for a value for **Net Service**, and you can then enter one of the following:
 - Enter the Net Service Name for this database if you have defined a Net Service Name in a `tnsnames.ora` file and specified the location of that file in a `TNS_ADMIN` environment variable.
 - Enter the string `%manual%` to let the script prompt you for the following: **Host name**, **Port** and **Service name**.
 - Enter the actual connection string directly on a single line if you have more to provide than just a host, port and service name. For example:

```
(DESCRIPTION = (ADDRESS = (PROTOCOL = TCP) (HOST = myhost) (PORT = 1521)) (CONNECT_DATA = (SERVICE_NAME = ora)))
```

3. Run the following PowerShell command, following the instructions that appear:

```
& '.\Install Infoshare Backend For Frontend database.ps1'
```

By completing this step, you have created the Backend for Frontend database.

Creating the Metrics database

Create the Metrics database using the provided PowerShell script.

Before you begin

- To complete this task, you need access to a database server machine that runs a supported database version. Database support is the same as for Content Manager.
- To run PowerShell database scripts for this database, the machine must meet the requirements described in "Creating databases for Content Manager security" on page 62.

About this task

Metrics is a feature that gives customers a variety of metrics, extracted from the content they create. The feature extracts technical documentation metrics that consist of productivity metrics as well as a Return on Investment value, which is based on the level of content reuse that is measured. Gathered data is collected and aggregated in the Metrics database. The Metrics web service fetches the data from the database and serves it up to its clients.

Note that for SQL Server databases, the Metrics database creation script sets the recovery model for the Metrics database to "Simple" rather than the default "Full". If your organization's policy is to use a "Full" recovery model (that is, an Always On availability group), please allow a "Simple" recovery model for the duration of initial load, in order to optimize performance.

Procedure

1. On your database server machine, open a PowerShell prompt.
2. For Oracle databases, specify a host, port, service name and other connection information for the PowerShell script, either *before* or *while* running the script:
 - *Before* you run the script, you can define a variable in PowerShell, let's say `$MyDatabaseServer`, and set it to your connection string. When you invoke the script, you then append the string `-DatabaseServer $MyDatabaseServer` to the PowerShell command.
 - Alternatively, you can just invoke the script as is, and *while* you run the script, PowerShell prompts you for a value for **Net Service**, and you can then enter one of the following:
 - Enter the Net Service Name for this database if you have defined a Net Service Name in a `tnsnames.ora` file and specified the location of that file in a `TNS_ADMIN` environment variable.
 - Enter the string `%manual%` to let the script prompt you for the following: **Host name**, **Port** and **Service name**.
 - Enter the actual connection string directly on a single line if you have more to provide than just a host, port and service name. For example:

```
(DESCRIPTION = (ADDRESS = (PROTOCOL = TCP) (HOST = myhost) (PORT = 1521)) (CONNECT_DATA = (SERVICE_NAME = ora)))
```

3. Run the following PowerShell command, following the instructions that appear:

```
& '.\Install Infoshare Metrics database.ps1'
```

By completing this step, you have created the Metrics database.

Installing the Content Manager server

You must install and configure the application and web server to use the Content Manager application, allowing you to connect to the repository.

Most of the Content Manager server installation process is automated. At the end of the process, some options must be set manually.

Be sure to check the installation requirements before initiating the application server installation.

Configuring database connection strings

Before installing the Content Manager software, you need to configure the connection between the application server and the Content Manager database. The connection is defined with a database connection string.

The topics in this section explain in detail the tasks involved in configuring connection strings.

Important: If you are upgrading to Tridion Docs 15.1 from a version earlier than release 15, you must create a *new* connection string. You cannot reuse an existing string in this upgrade scenario because Tridion Docs 15 introduces a stricter policy for keywords in connection strings.

The following steps summarize the process in the order the tasks must be performed:

1. Create the connection string according to the requirements for the type of database you are using, that is, for Microsoft SQL Server or Oracle.
2. If using an Oracle database, update the `tnsnames.ora` file.
3. Add the connection string to the `inputparameter.xml` file.

The final step is part of the broader task of editing the `inputparameter.xml` file. The next topic in this section provides the details on this file. Once that is done, you are ready to run the Content Manager InstallTool. After completing the installation process, the system adds the connection string to the `connect` setting in the server's registry.

Sample database connection strings

This topic provides examples of connection strings for SQL Server and Oracle databases.

Connection strings for SQL Server

The following is an example of a standard connection string for Microsoft SQL Server:

```
Provider=MSOLEDBSQL.1;Data Source=myServerAddress;Initial Catalog=myDataBase;User Id=myUsername;Password=myPassword;
```

The following is an example of a standard connection string for Microsoft SQL Server that includes a trusted connection using Integrated Security:

```
Provider=MSOLEDBSQL.1;Data Source=myServerAddress;Initial Catalog=myDataBase  
;Integrated Security=SSPI;
```

When using Integrated Security, the user specified in the Input Parameter `osUser` used by `InstallTool`, should have sufficient privileges on the database.

Note:

- The provider shown is the Microsoft OLE DB Driver for SQL Server. Only this provider is supported.
 - Communication between the application server and the database server is (by default) encrypted.
One of the following is required:
 - A valid certificate issued by a certificate authority (CA) is installed on the Microsoft SQL Server.
 - The connection string contains "Trust server certificate = True" to indicate that you trust the server with a self-signed certificate.
 - Ensure that the connection string does not contain any of the following as keywords: *Access Token*, *Initial File Name* and *Server SPN*.
-

Connection strings for Oracle

The following is an example of a standard connection string for Oracle:

```
Provider=OraOLEDB.Oracle.1;Data Source=MyOracleDB;User Id=myUsername;  
Password=myPassword;
```

The following is an example of a standard connection string for Oracle with OS Authentication:

```
Provider=OraOLEDB.Oracle.1;Persist Security Info=False;User ID=/;Data Source  
=MyOracleDB
```

Note:

- The provider shown is the Oracle Provider for OLE DB. Only this provider is supported.
 - The data source is the *net_service_name* entry in the *oracle_home\network\admin\tnsnames.ora* file.
-

Editing `tnsnames.ora` for an Oracle database

For Oracle databases, the `tnsnames.ora` file defines the information for a connection to the database server and to the database instance for the Content Manager repository. Modify the file on the Oracle database server, and on all systems that communicate with the Oracle database server.

About this task

If the Oracle database server and client software are installed on the same system, you must edit the `tnsnames.ora` file under each Oracle home directory.

Procedure

1. Sign in to the server as an administrator user.
2. Go to the folder `ORACLEHOME\network\admin\`, where `ORACLEHOME` is the Oracle home directory.
3. If this folder does not yet contain a file called `tnsnames.ora`, create an empty plain-text document and save it as `tnsnames.ora` in this folder.
4. Open `ORACLEHOME\network\admin\tnsnames.ora` in a plain-text editor.
5. Add the following to the file. Make sure that the first line starts on position 1, that is, that it contains no leading whitespace.

```
NETSERVICENAME =
(DESCRIPTION =
  (ADDRESS_LIST =
    (ADDRESS = (PROTOCOL = TCP)
      (HOST = HOSTNAME)
      (PORT = 1521))
  )
(CONNECT_DATA =
  (SERVICE_NAME = SERVICENAME)
)
)
```

where:

- `NETSERVICENAME` is an alias, for example, `ISH.WORLD`, that is used for a connect descriptor.
- `HOSTNAME` is the IP address or name of the database server, for example, `devserver01` or `127.0.0.1`.
- `SERVICENAME` is a combination of the `db_name` and `db_domain` values in the `C:\oracle\admin\ISH\pfile\PFIL\initISH.ora` file. For example:

```
SERVICE_NAME = ISH.ORASERVER.DOMAIN.NAME
```

where `ISH` is the `db_name` value and `ORASERVER.DOMAIN.NAME` is the `db_domain` value in the `initISH.ora` file.

6. Save and close the file.

Preparing the `inputparameters.xml` file

The `inputparameters.xml` file stores parameters that are used by the Content Manager installer; therefore, the file must accurately reflect your environment before proceeding with installation. Only the mandatory parameters need to be considered in the vast majority of installations. The optional parameters cover rare and advanced cases.

Before you begin

Before modifying the `inputparameters.xml` file, you need to do the following:

- Obtain and install the certificate.
- Configure HTTPS bindings.

Procedure

1. From the `__InstallTool` folder of the installation directory, open the `inputparameters.xml` file for editing.
2. Edit the values of all mandatory parameters. Refer to the related topic for details. Each parameter in the `inputparameters.xml` file has the following syntax:

```
<param name="parameter">
  <currentvalue>value</currentvalue>
  <defaultvalue>example_value</defaultvalue>
  <description>description_of_how_used</description>
  <validate>if_validated</validate>
</param>
```

The XML elements perform the following functions:

<currentvalue>

Contains the value that is used by the Content Manager installer.

<defaultvalue>

Contains a predefined value as an example. Do not use the predefined value as a default value; its only purpose is to serve as an example.

<description>

Contains details describing how the current value of the parameter is used.

<validate>

Defines whether the value of the parameter is validated or not. If the element is empty, no validation is performed. The `<validate>` values are provided, and they should not be modified.

3. Edit the values of all optional parameters, as needed. Refer to the related topic for details.
4. Save and close the file.

Mandatory input parameters in `inputparameters.xml`

This section lists and describes the main input parameters contained in the `inputparameters.xml` file, the ones you need to set for any installation. Some of these input parameters are mandatory: you need to set them in order for the installation to work correctly.

osuser

The username of the designated operating system user. This user must be a local administrator and have the correct regional settings.

ospassword

The password of the designated operating system user. Set the password so that it never expires.

connectstring

The connection string for the Content Manager database (InfoShareCM). See the default suggestion or the documentation under "Sample database connection strings." For Oracle, 'Provider=OraOLEDB.Oracle.1;Data Source=MyOracleDB;User Id=myUsername;Password=myPassword;' should be used.

ishamconnectstring

The connection string for the Access Management database (InfoShareAM).

ishbffconnectstring

The connection string for the Backend-for-Frontend database (InfoShareBFF).

ishidconnectstring

The connection string for the Tridion Docs Identity Provider database (InfoShareID).

ishmetricsconnectstring

The connection string for the Tridion Docs Metrics database (InfoShareMetrics).

apppath

The root directory for the Content Manager installation. By default, this is set to `C:\InfoShare`.

baseurl

The first part of the URL that your InfoShare users will need to browse to use it, `https://ish.example.com` for example.

ps_java_home

The full path to an OpenJDK `JAVA_HOME` folder. This allows you to specify your path and, if needed, switch between compatible versions. Refer to the documentation for the version tested against.

Note: Do not use environment variables or put your file path in quotation marks.

serviceusername

Specify an existing InfoShare internal user profile `Username` to use for services like `TranslationBuilder`. Authentication happens over `AuthenticationContext` or using the deprecated WS-Trust authentication.

servicepassword

Specify an existing InfoShare internal user profile Password to use for services like TranslationBuilder. Authentication happens over AuthenticationContext or deprecated WS-Trust authentication.

serviceaccountclientid

Specify the InfoShare user profile Username to use for services like TranslationOrganizer. When the install tool for Access Management (ISHAM) is run, the value specified here is used, and thus becomes the service account client ID for requesting an access token from Access Management.

serviceaccountclientsecret

Specify any secret of your choice (it could be a GUID, for example) to use for services like TranslationOrganizer. When the install tool for Access Management (ISHAM) is run, the value specified here is used, and thus becomes the service account secret for requesting an access token from Access Management.

metricsserviceclientid

Specify the client identifier that the background task service should use to communicate with the Metrics API. When the install tool for Access Management (ISHAM) is run, the value specified here is used, and thus becomes the Metrics service client ID for requesting an access token from Access Management.

metricsserviceclientsecret

Specify any secret of your choice (it could be a GUID, for example) to use for communicating with the Metrics API. When the install tool for Access Management (ISHAM) is run, the value specified here is used, and thus becomes the Metrics service client secret for requesting an access token from Access Management.

Optional input parameters in `inputparameters.xml`

By default, the file `inputparameters.xml` contains only a set of mandatory properties. Optional parameters are either calculated by Content Manager, or they have a predefined default value. This section lists and describes the optional input parameters that you can set in the `inputparameters.xml` file. Only Content Manager experts should change these parameters.

Optional parameters

Note: When you provide a value to a parameter that is calculated by default, the parameter is set to your value and is no longer calculated.

Name	Description	Default value
projectsuffix	Whenever more than one project is installed, the <code>projectsuffix</code> value indicates the project. Remember to make web application names and service ports unique as well. The value of this parameter is given as <code>PROJECTSUFFIX</code> in the rest of this table.	(none)
webpath	The path of the folder in which the website folder is created.	<code>APPPATH</code> (calculated)
datapath	The path of the folder in which the data folder is created. For example, when the datapath is <code>c:\InfoShare</code> the logs will be created in the folder <code>c:\InfoShare\Data\Logs\</code> .	<code>APPPATH</code> (calculated)
workspacepath	This path is a temporary folder in which all the folders and files are copied and modified before the actual installation.	<code>APPPATH\Workspace</code> (calculated)
infosharecswebappname	The name of the web application that offers Organize Space, Draft Space and Review Space Services.	<code>ISHCS + PROJECTSUFFIX</code>
infoshareauthorwebappname	The name of the Content Manager web application hosting ClientConfig and ASP.NET pages.	<code>ISHCM + PROJECTSUFFIX</code>
infosharewswebappname	The name of the web application for Content Manager web services.	<code>ISHWS + PROJECTSUFFIX</code>
infosharestswebappname	The name of the web application with the deprecated Content Manager Secure Token Service (STS).	<code>ISHSTS + PROJECTSUFFIX</code>
websitename	The name of the website in which all web applications will be created.	Default Web Site
infoshareidwebappname	The name of the web application for the Tridion Docs Identity Provider.	<code>ISHID + PROJECTSUFFIX</code>
infoshareextwebappname	The name of the web application with the Web Extensions Service hosting customizations for Organize Space.	<code>ISHEXT + PROJECTSUFFIX</code>
infoshareamwebappname	The name of the Access Management web application.	<code>ISHAM + PROJECTSUFFIX</code>
infosharemetricswebappname	The name of the Metrics web application.	<code>ISHMT + PROJECTSUFFIX</code>

Name	Description	Default value
localservicehostname	Indicates the local service hostname part of the base URL. This can be <code>localhost</code> or the machine name. It will be used by all service side components that access the WCF Services on the same box.	the NetBIOS name of this local computer (calculated)
ps_fo_processor	The fully qualified file name of the XSL-FO processor, for example <code>C:\Program Files\AntennaHouse\AHFormatterV6\AHFCmd.exe</code> .	the highest installed version in <code>%ProgramFiles%</code> (calculated).
ps_htmlhelp_processor	The fully qualified file name of the HTML Help processor.	<code>C:\Program Files (x86)\HTML Help Workshop\hhc.exe</code> Note: Do not use environment variables or quotation marks.
ps_javahelp_home	The full path to a JavaHelp <code>JHHOME</code> folder, used when you want to publish with the JavaHelp output type.	<code>C:\javahelp\jh2.0</code> Note: Do not use environment variables or quotation marks.
solrlucene_service_port	The port that the <code>SolrLucene</code> service uses. This port must be unique for each Content Manager instance installed on a server.	8983
basehostname	The hostname part of the base URL. This value will be calculated using <code>BASEURL</code> as input, stripping the protocol <code>http</code> or <code>https</code> (e.g. <code>ish.example.com</code>)	<code>BASEURL</code> (calculated)
servicecertificatethumbprint	The thumbprint of an already installed certificate (e.g. <code>A43489159A520F0D93D032CCAF37E7FE20A8B419</code>) for unique service identification. You can repurpose your SSL certificate. Note that all your linked web application servers in a farm should offer the same trusted certificate.	from HTTPS binding of <code>websitename</code> (<code>20A8B419</code>)
servicecertificatevalidationmode	The validation mode specified here decides how the application-to-application communication validates service certificates (specified in <code>servicecertificatethumbprint</code>). The allowed options are: <code>ChainTrust</code> , <code>PeerTrust</code> , <code>PeerOrChainTrust</code> or <code>None</code> . Setting the mode to <code>None</code> causes any certificate to be accepted.	<code>ChainTrust</code>

Name	Description	Default value
servicecertificatesubjectname	Specify the subject name of an already installed certificate for unique service identification. You can repurpose your SSL certificate. Note that all your linked web application servers in a farm should offer the same trusted certificate.	from HTTPS binding of websitename

Executing the InstallTool

Use the Content Manager InstallTool to install and merge all standard and customer specific project files.

Before you begin

In the context of a Content Manager install or uninstall operation, before you run InstallTool you need to make sure the Microsoft Distributed Transaction Coordinator MSDTC service is running.

Procedure

1. Login to your Windows system as a Content Manager user with the Administrator user role.
2. In Windows Explorer, go to
C:\ISHCD\yyyymmdd.CD.InfoShare<version_num>\ProjectName.IT__InstallTool
3. Locate and double-click on **InstallTool.exe**.
4. Select the **Install** option by entering the number **2**.
5. Hit enter to respond to all questions; the default options should be sufficient.

All standard and customer specific project files are merged and installed. All required services have to be started manually (the Crawler, SolrLucene, IISAdmin, W3SVC).

Identifying connection issues caused by reverse proxies

Various reverse proxy servers can be used in combination with Content Manager. Using reverse proxy servers may result in connection problems to the Content Manager repository. You can check the BASEURL to verify that it is not causing any problem in your internet browser.

When you identify reverse proxy servers, verify that the following URLs do not cause any problems in the internet browser:

- BASEURL/ISHWS/Application.asmx?wsdl
- BASEURL/ISHWS/Application.asmx?disco

The BASEURL is specified in the `inputparameters.xml` file used by the Content Manager installer.

The `BASEURL` must use the `https` schema. It must also reference a hostname that is valid for the SSL certificate.

For example if the server has a SSL certificate configured with `CN=example.com` then the `BASEURL` must be `https://example.com`.

Example:

```
<param name="baseurl">
<currentvalue>https://example.com</currentvalue>
<defaultvalue>https://example.com</defaultvalue>
<validate/>
</param>
```

Make sure that the URLs are accessible by your users.

Installing desktop client tools

You can choose to install desktop client tools (Authoring Bridge, Publication Manager, Condition Manager and Content Importer) based on the role and responsibilities of the user. The versions of the desktop clients tools must match the version of Content Manager installed on the server.

Uninstalling desktop client tools (upgrade only)

If you are upgrading Content Manager, first uninstall your existing desktop client tools from the Windows Settings, in the **Apps & features** screen. The specific names of the items depend on the version from which you are upgrading, but will include the name of the product and the strings "Condition Manager," "Content Importer," "Publication Manager," and "Connector" or "Authoring Bridge".

Installing the Authoring Bridge

The Authoring Bridge is used to access the repository using an authoring tool.

About this task

Choose the Authoring Bridge installer for the XML editor software that you are using (XMetaL or Oxygen). The type and version of the editor you are using must be supported by the installed version of Content Manager.

If an incompatible version of the .NET runtime framework is installed, the installer will install a correct one after your validation.

The install package's names match the following format, one for each compatible XML Editor:

- `<date>.AuthoringBridge.<version>-XMetaL-Connector.msi`
- `<date>.AuthoringBridge.<version>-oXygen-Connector.msi`

The development kit's executable name matches the following format:

- `<date>.AuthoringBridgeSDK.<version>.exe`

Procedure

1. Double-click the Authoring Bridge install package, or **Setup Wizard**, and follow the proposed list of steps. After you hit the **Finish** button, the installation is complete and the Tridion Docs menu is now available in your authoring tool's menu bar.

Results

When you first try to access the Repository from your authoring tool, you will be requested to specify a user account in order to establish the connection.

For uninstall, be aware of the following:

- If you are using XMetaL on Windows, you must uninstall the Authoring Bridge before uninstalling XMetaL.
- If the Authoring Bridge is uninstalled, the Tridion Docs menu will remain in the menu bar, with all menu options greyed out. You must start XMetaL while pressing the **CTRL** key in order to have XMetaL clean up the menu bar and remove the Tridion Docs menu.

Installing Publication Manager

The publication manager is used to create, modify, check the status of, and produce publications in various formats.

About this task

If an incompatible version of the .NET runtime framework is installed, the installer will install a correct one after your validation.

The install package's name matches the following format: `<date>.PublicationManager.<version>.msi`

Procedure

1. Double-click the Publication Manager install package, or **Setup Wizard**, and follow the proposed list of steps. After you hit the **Finish** button, the installation is complete and Publication Manager is now available for you to use.

Installing Condition Manager

The Condition Manager is used to create and manage conditions for your publications.

About this task

If an incompatible version of the .NET runtime framework is installed, the installer will install a correct one after your validation.

The install package's name matches the following format: `<date>.ConditionManager.<version>.msi`

Procedure

1. Double-click the Condition Manager install package, or **Setup Wizard**, and follow the proposed list of steps.
2. Select the **Enable Synchronization** option when proposed (on the tab where you specify the installation folder). Content Manager can synchronize the set of conditions with definitions from another system. Synchronization needs to be configured separately, **Enable Synchronization** only makes the menu items available in the application.
3. After you hit the **Finish** button, the installation is complete and Condition Manager is now available for you to use.

Installing Content Importer

Content Importer helps you import content through Organize Space commands.

About this task

If an incompatible version of the .NET runtime framework is installed, the installer will install a correct one after your validation.

The install package's name matches the following format: `DATE.ContentImporter.VERSION.msi`, where *DATE* is a date and *VERSION* is the version of Content Importer.

Procedure

1. Double-click the Content Importer install package, or **Setup Wizard**, and follow the proposed list of steps. After you hit the **Finish** button, the installation is complete.

After the Content Manager installation

After you complete the installation of your Content Manager server, perform a number of tasks to help you verify the installation, and to configure the components that you have just installed.

Creating a ServiceUser user

Creating a ServiceUser user is a mandatory action for translation services, and for the interaction between Content Manager and a delivery platform.

About this task

The ServiceUser user must be available with all user groups because it needs to be used by important services. User roles must also be added (e.g. the TRANSLATORSERVICE role is necessary for using the translation services).

Procedure

1. Sign in to Organize Space.
2. On the second tab level, select the **Users** tab.
3. On the third tab level, select the **Users** tab.
4. Click **New** in the toolbar in the right pane to display the User Properties dialog.
5. In the User Properties dialog:
 - As **User name**, enter `ServiceUser`.
 - As **Password**, enter a password that is specified in `inputparameters.xml`.
 - As **Roles**, select all roles that this ServiceUser needs. A basic set would be `TRANSLATORSERVICE`, `Translator`, and `Administrator`.
 - As **Groups**, select all available groups.
 - As **User type**, enter `Internal`.
 - As **External ID**, enter `ClientId`, where `ClientId` is a client identifier of the Access Management service account API Client (ServiceUser).
 - Select **OK** to apply your changes and close the dialog.

Reapplying custom Content Manager Add-ons

If you have developed custom Add-ons for Content Manager, recompile and reapply them after you have upgraded the Content Manager that they extend. Perform this task for each of your custom Add-ons for Content Manager.

Before you begin

You must have a copy of your Add-on ZIP file available, either as a resource with a URL (say in an S3 bucket) or as a physical file on your local file system.

Procedure

1. Recompile any code in your Add-on, to ensure that your code still works with the new set of prerequisites required by the new release.
2. Test the functionality of your Add-on to verify that it continues to work with the upgraded Content Manager.

Synchronizing the Content Manager database with Metrics storage

In order to use the Metrics feature, your Content Manager database must be synchronized with your Metrics storage. Depending on your installation or upgrade scenario, you may need to perform the synchronization yourself, by running a script called `SynchronizeMetrics.ps1`.

Before you begin

To perform this task, you must have set up ISHRemote 8.1.0 or later. For more information, refer to <https://github.com/RWS/ISHRemote>.

About this task

You must run a synchronization script if any of the following is true:

- You are performing a fresh installation of Tridion Docs with a sample database called Mobile Phones pre-installed.
- You are upgrading from a release older than Tridion Docs 15.1
- You are applying Tridion Docs 15.1 Update 1 to your existing Tridion Docs 15.1 setup.

You do not need to run a synchronization script if you are performing a fresh installation of Tridion Docs with an empty database.

Procedure

1. Open a PowerShell prompt.
2. On your installation media, go to the folder `Common\ DatabaseIndependent\ Examples\ Metrics\`.
3. Use the ISHRemote `New-IshSession` command to create a new session. For more information about this command, enter `Get-Help New-IshSession -Full`.
4. Run the synchronization script by executing the following command:

```
SynchronizeMetrics.ps1 -ishSession SESSION -Transcript  
-TranscriptFilePath FILEPATH
```

where *SESSION* is the name of the variable (for example, `$ishSession`) in which you stored the return value of your `New-IshSession`.

The following switches in the command are optional:

Transcript

Causes the script to log its activities to a separate text file. If you omit this switch, no text file is created.

TranscriptFilePath

Use this switch only if the `Transcript` switch is also used. `TranscriptFilePath` specifies a path and filename for the logfile in *FILEPATH*. For example, `-TranscriptPath "c:\temp\mylog.txt"`

If you omit this switch, the log file is written to the location from which you are executing the script, and the filename will be `SynchronizeMetrics.ps1.log`

The script goes through the entire repository and creates background tasks to synchronize the Content Manager repository with Metrics storage.

What to do next

Note the following:

- If you run into any trouble running the script, you can rerun the script with the `-filePath` switch. Use this switch to specify a specific node folder in your repository. This folder, including any of its subfolders, will then be synchronized. For example, your command might be `SynchronizeMetrics.ps1 -ishSession $ishSession -folderPath "General\MyFolder"`

- To see a list of the folders that the script intends to synchronize, without actually creating the backgrounds to do so, add a `-WhatIf` switch to your command.

Verifying Microsoft SQL System Administration role permissions

If you use Microsoft SQL Server as your database, then after installing Content Manager, grant the `isource` user system administrator permissions. This ensures that the database upgrade tool (DBUpgradeTool or DBUT) works properly.

About this task

To allow DBUT to fully execute all necessary tasks to update your Microsoft SQL Server database now and for each new release, follow the procedure below to ensure the database user has the necessary permissions.

Procedure

1. Access the **SQL Server Management Studio**.

Windows 2012: To access the **SQL Server Management Studio** if not readily accessible, use the **Windows Powershell** icon on the bottom toolbar then at the prompt type: **Ssms.exe**.

Note: If prompted and required, connect to the server.

2. Under the folder for the MSSQL server in the left pane, open **Security > Logins**.
3. Right-click on the **isource** user and select **Properties**.
A Login Properties - isource window displays.
4. In the left pane of the Login Properties - isource window select **Server Roles**.
5. In the right pane for Server Roles select **public** and **sysadmin**.
6. Click **OK**.
7. Click **File > Exit** to exit and close the Microsoft Server Management window.

Running DBUpgradeTool for maintenance

After installing Content Manager, use DBUpgradeTool (DBUT) to perform an overall verification of the database, to update database objects such as views, indexes, packages and stored procedures, and to modify metadata structures.

Before you begin

- The `isource` database user must have the System Administrator privilege.
- The Content Manager server and Content Manager database must be available (up and running), complete and correctly installed. The installation ensures that the upgrade files and connections are in place to allow a successful upgrade.
- DBUT has exclusive access to the Content Manager database. That means that before running the tool, you should stop all components and services, such as InfoShare Crawler, on all servers.

Procedure

1. Sign in to the Content Manager application server as a Windows user with the Administrator user role.
2. In Windows Explorer, go to the Content Manager installation directory, then go to `\App\Setup\DBUpgradeTool\`.
3. Run `DBUpgradeTool.exe`
4. Only if you use ADFS, use DBUT to configure the `FishExternalID` of the administrator user with a value such as *domain\username*, for the user who has to sign in to the system as administrator:
 - a. In DBUT, select option 1: **Maintenance**.
 - b. Select option 5: **Append** an user's external ID for initial STS sign-in.
 - c. Choose the installation and then fill in the appropriate value for the Content Manager admin user.
5. If you performed an upgrade, select the **DatabaseUpgrade** option.
6. Press **Enter** to respond to a series of questions; the default options are sufficient for the following questions:
 - Select your recently installed project (thereby selecting the database location and user, upgrade script paths, version and so on).
 - Default for the application.

The result is an upgrade from an older or same version to the installed version when applicable. The application pool needs to be restarted after a DBUT run.

Troubleshooting DBUpgradeTool

You may encounter issues during DBUT execution for database upgrade purposes.

Execution is interrupted

If the DBUT suddenly dies, it results in a hanging database upgrade logged in to the database. All other attempts to upgrade will fail since only one upgrade process is permitted to run at a time.

To force an undo of a hanging update, execute DBUT then select **Maintenance > Terminate** and your current project.

Current user isource warnings

The following warnings can occur in DBUT:

- WARNING: The current user "isource" does not have permission to disable the standard database job for InfoShare.
- WARNING: The current user "isource" does not have permission to install the standard database job for InfoShare. Ask a System Administrator to manually execute `ISH_CreateStandardInfoShareJob.sql` and `ISH_EnableStandardInfoShareJob.Sql` to create and enable the standard InfoShare job!
- WARNING: The current user "isource" does not have permission to enable the standard database job for InfoShare.

These warnings are returned when the user executing DBUT has not enough rights to access/create database jobs.

- Creating a database job requires a database administrator to execute `CD-Package\Database\InfoShareCM\Common\<SQLServerVersion>\Create\ISH_CreateStandardInfoShareJob.sql` and `CD-Package\Database\InfoShareAM\Common\<SQLServerVersion>\Create\ISH_CreateStandardInfoShareJob.sql`
- Enabling a database job requires a database administrator to execute `CD-Package\Database\InfoShareCM\Common\<SQLServerVersion>\Create\ISH_EnableStandardInfoShareJob.Sql` and `CD-Package\Database\InfoShareAM\Common\<SQLServerVersion>\Create\ISH_EnableStandardInfoShareJob.Sql`

Requesting assistance

In case you need to request assistance, you need to provide the following information:

- A screenshot of the failed execution of `DBUpgradeTool`.
- The log file: `\App\Setup\DBUpgradeTool\DBUpgradeTool.log`

Installing ISHDeploy and ISHRemote

When installing Tridion Docs 15.1, you need to install the ISHDeploy and ISHRemote PowerShell modules on the Content Manager application server. The modules are needed to run the scripts delivered with Tridion Docs.

Before you begin

- Microsoft Windows PowerShell 5.1 (part of Windows Management Framework 5.1)
To quickly check your installed PowerShell version, execute the following script:

```
$PSVersionTable
```

If your operating system has an earlier version of PowerShell, then you need to install PowerShell 5.1.

- You must be logged on as an administrator user to perform this task.

About this task

ISHDeploy is a PowerShell module that enables the **code as configuration** concept for Tridion Docs. You can use ISHDeploy cmdlets for all basic setup operations, and for many advanced configuration tasks. Although manual configuration is still available, we recommend you use ISHDeploy for improved simplicity and safety. ISHDeploy also gives you access to automation.

ISHRemote is a PowerShell module that enables business automation for Tridion Docs. It's constructed close to the Web Services API to:

- allow business logic automation, ranging from triggering publishing into the continuous integration pipeline to legacy data correction, up to provisioning
- showcase code examples and API best practices

All scripts delivered with Tridion Docs, such as those in the `..\DatabaseIndependent\Examples\` folder, expect ISHDeploy and ISHRemote to be installed. Install both of the PowerShell modules using the installation script delivered with your installation package or downloaded from the [PowerShell Gallery](#) (always the latest).

Procedure

1. On the Content Manager application server, open a PowerShell prompt.
2. Run one of the following PowerShell scripts:

InstallPowerShellLibrariesFromLocal.ps1

This script is provided in the local NuGet packages delivered with the product. Get it from the following folder: `c:\InfoShare\App\Setup\PowerShell\Repository`

To run the script, use the following command:

```
& '.\InstallPowerShellLibrariesFromLocal.ps1'
```

InstallPowerShellLibrariesFromPSGallery.ps1

This script always installs the *latest* versions of ISHDeploy and ISHRemote. You can download from [PowerShell Gallery](#).

To run the script, use the following command:

```
& '.\InstallPowerShellLibrariesFromPSGallery.ps1'
```

Both ISHDeploy and ISHRemote are now installed.

Checking translation services roles and privileges

An active TRANSLATORSERVICE role is necessary for translation services (TranslationOrganizer, TranslationBuilder) to operate. This role is part of the out-of-the-box settings for Content Manager 10.0.0 and later. As from Tridion Docs 15, the user used for translation services must have an "Administrator" user role, or be a part of any other role that as "System Administrator" privilege or "Translation Mangement" privilege. In case

TRANSLATIONSERVICE role needs to be created with all status transitions, follow the procedure:

Procedure

1. Sign in to Organize Space as a user with administrator-level credentials.
2. On the top tab level, select the **Settings** tab.
3. On the second tab level, select the **Users** tab.
4. On the third tab level, select the **User Roles** tab.
5. Do one of the following:
 - If *TRANSLATORSERVICE* is part of the list, select it and select **Properties** from the button toolbar. In the dialog that opens, make sure that **Active** is selected.
 - If *TRANSLATORSERVICE* is not part of the list, create it by selecting **New** from the button toolbar and, in the dialog that opens, specifying *TRANSLATORSERVICE* in the **Name** field. Then select **OK** to close the dialog and apply your changes.
6. On the second tab level, select the **XML Settings** tab.
7. On the third tab level, select the **Statuses** tab.
8. Check that the following status transitions are configured as <FromStatus> sections in the <Transitions> section of the XML you see:

From Status	To Status	User Role
To be translated	In translation	TRANSLATORSERVICE
In translation	Translation in review	TRANSLATORSERVICE
In translation	Translation approved	TRANSLATORSERVICE
Translation in review	Translation approved	TRANSLATORSERVICE
Translation in review	Translation rejected	TRANSLATORSERVICE
Translation rejected	In translation	TRANSLATORSERVICE

If you see XML for all these transitions, then no other action is required.

9. However, if any of these transitions are not part of the list, create them by adding the following XML fragment within the <Transitions> section:

```
<FromStatus ref="FROMSTATUS" userrole="TRANSLATORSERVICE">
  <ToStatus ref="TOSTATUS" />
</FromStatus>
```

where *FROMSTATUS* is the item in the **From Status** column above for the missing transition, and *TOSTATUS* is the item in the **To Status** column above for the missing transition.

10. If you made any changes, select **Save** to commit those changes.

Enabling Content Manager user interfaces and features

After installing Content Manager, you can individually enable the individual user interfaces and subfeatures that are part of Collective Spaces.

Enabling Draft Space

Enable Draft Space by running an ISHDeploy command and setting the **Enable Draft Space** flag in the Organize Space user interface.

Before you begin

To learn how to access and use ISHDeploy, refer to the section on "" on page 0.

About this task

Draft Space is one of the two applications that are grouped under the name Collective Spaces.

Procedure

1. In a Powershell command shell, enter the following command:

```
Enable-ISHUICollectiveSpaces -DraftSpace -ISHDeployment ISHDEPLOYMENT
```

where *ISHDEPLOYMENT* is the deployment you want to use. (If you have only one deployment, you can omit the *-ISHDeployment* parameter and its value.)

2. Enable Draft Space from the Organize Space user interface by doing the following:
 - a. On the top tab level, select the **Settings** tab.
 - b. On the second tab level, select the **System** tab.
 - c. On the third tab level, select the **Default Settings** tab.
 - d. In the **Optional features** area, select **Draft Space (paid)**.
 - e. Select **Save** to apply your changes.

Results

You now have access to Draft Space for web browser-based content authoring.

Enabling Review Space

Enable Review Space by running an ISHDeploy command and setting the **Enable Review Space** flag in the Organize Space user interface.

Before you begin

To learn how to access and use ISHDeploy, refer to the section on "" on page 0.

About this task

Review Space is one of the two applications that are grouped under the name Collective Spaces.

Procedure

1. In a Powershell command shell, enter the following command:

```
Enable-ISHUICollectiveSpaces -ReviewSpace -ISHDeployment ISHDEPLOYMENT
```

where *ISHDEPLOYMENT* is the deployment you want to use. (If you have only one deployment, you can omit the `-ISHDeployment` parameter and its value.)

2. Enable Review Space from the Organize Space user interface by doing the following:
 - a. On the top tab level, select the **Settings** tab.
 - b. On the second tab level, select the **System** tab.
 - c. On the third tab level, select the **Default Settings** tab.
 - d. In the **Optional features** area, select **Review Space (paid)**.
 - e. Select **Save** to apply your changes.

Results

You now have access to Review Space for web browser-based content reviewing.

Enabling Document History for Draft Space

Enable Document History for Draft Space by running an ISHDeploy command and setting the **Enable Draft Space Document History** flag in the Organize Space user interface.

Before you begin

In order to be able to use Document History for Draft Space, Draft Space must be enabled.

To learn how to access and use ISHDeploy, refer to the section on "" on page 0.

About this task

Document History is a Collective Spaces feature. It lets you trace the history of each document in detail, but you should only enable it if you have the required license for this feature.

Procedure

1. In a Powershell command shell, enter the following command:

```
Enable-ISHUICollectiveSpaces -DocumentHistoryForDraftSpace  
-ISHDeployment ISHDEPLOYMENT
```

where *ISHDEPLOYMENT* is the deployment you want to use. (If you have only one deployment, you can omit the `-ISHDeployment` parameter and its value.)

2. Enable Document History for Draft Space from the Organize Space user interface by doing the following:
 - a. On the top tab level, select the **Settings** tab.
 - b. On the second tab level, select the **System** tab.
 - c. On the third tab level, select the **Default Settings** tab.
 - d. In the **Optional features** area, select **Draft Space document history (paid)**.
 - e. Select **Save** to apply your changes.

Results

You now have access to Document History for web browser-based content authoring. The **Show Changes** option is now enabled for documents in Draft Space.

Enabling Document History for Review Space

Enable Document History for Review Space by running an ISHDeploy command and setting the **Enable Review Space Document History** flag in the Organize Space user interface.

Before you begin

In order to be able to use Document History for Review Space, Review Space must be enabled.

To learn how to access and use ISHDeploy, refer to the section on "" on page 0.

About this task

Document History is a Collective Spaces feature. It lets you trace the history of each document in detail, but you should only enable it if you have the required license for this feature.

Procedure

1. In a Powershell command shell, enter the following command:

```
Enable-ISHUICollectiveSpaces -DocumentHistoryForReviewSpace  
-ISHDeployment ISHDEPLOYMENT
```

where *ISHDEPLOYMENT* is the deployment you want to use. (If you have only one deployment, you can omit the `-ISHDeployment` parameter and its value.)

2. Enable Document History for Review Space from the Organize Space user interface by doing the following:
 - a. On the top tab level, select the **Settings** tab.

- b. On the second tab level, select the **System** tab.
- c. On the third tab level, select the **Default Settings** tab.
- d. In the **Optional features** area, select **Review Space document history (paid)**.
- e. Select **Save** to apply your changes.

Results

You now have access to Document History for web browser-based content reviewing. The **Show Changes** option is now enabled for documents in Review Space.

Setting the Collective Spaces URL for your accounts

Before you begin

As of SDL Tridion Docs 14 SP2, Publication Manager users can copy the Draft Space URL or Review Space URL of each topic to the clipboard. To enable this feature for an account, the Collective Spaces URL must be configured in the account settings.

Procedure

1. Start Publication Manager.
2. Select **Tools > Accounts**.
3. In the **Repository** tab, find the **Collective Spaces address** property.
4. Fill in the Collective Spaces URL and select **OK**.

Enabling services

After the installation has completed, services will not start automatically, since the database is not guaranteed to be in the right state until you run the DBUT tool. Also, you might decide not to start some services on the specific installation depending on the server role. To enable typical services, you can locate and run the `Enable-DefaultServices.ps1` script.

Before you begin

- The ISHDeploy module is installed.
- DBUT completed successfully.
- The Administrator setup completed successfully.
- The TRANSLATORSERVICE role is created and the translation status transitions have been assigned to it.
- You have System Administrator rights.

Procedure

1. Run the script `\App\Setup\Manage\Enable-DefaultServices.ps1`.
Typical services are started and the startup type is set to "Automatic (Delayed Start)".
The following are some of the typical services:
 - Trisoft InfoShare
 - Crawler One
 - Trisoft InfoShare SolrLucene
 - Trisoft InfoShare BackgroundTask One
 - Trisoft InfoShare TranslationBuilder One

Configure Security Token Service for authenticating WCF .SVC web services (deprecated)

The WCF .SVC web services require that you configure a Security Token Service (STS) for authentication, which uses ISHSTS as the default identity provider.

Using ISHDeploy is an alternative to the manual tasks described in this section.

Security Token Service for externalized authentication and Single Sign-On is deprecated as of Tridion Docs 15. Prior to Tridion Docs 15, the Content Manager user interfaces also used Security Token Service; however, these applications now use Tridion Access Management. At this time, only the WCF .SVC web services continue to use the deprecated Security Token Service.

Web Services requirements for Security Token Service

The WCF .SVC web services (ISHCM) require identifiers and certificates to configure Security Token Service.

Profile

WCF .SVC web services rely on an *Active profile* to do *Federated Authentication*. The profile refers to SOAP-based web services implementing the WS Trust protocol. Token encryption is mandatory.

Identifiers and encryption certificates

The web service ISHCM expects specific identifiers in combination with an encryption certificate to be configured on a Security Token Service.

The encryption certificate is the public key of the certificate referenced through the `servicecertificatethumbprint` input parameter.

The identifiers are as follows:

- `https://example.com/ISHWS/`

- <https://example.com/ISHWS/Wcf/API25/Application.svc>
- <https://example.com/ISHWS/Wcf/API25/Baseline.svc>
- <https://example.com/ISHWS/Wcf/API25/DocumentObj.svc>
- <https://example.com/ISHWS/Wcf/API25/EDT.svc>
- <https://example.com/ISHWS/Wcf/API25/EventMonitor.svc>
- <https://example.com/ISHWS/Wcf/API25/Folder.svc>
- <https://example.com/ISHWS/Wcf/API25/ListOfValues.svc>
- <https://example.com/ISHWS/Wcf/API25/MetadataBinding.svc>
- <https://example.com/ISHWS/Wcf/API25/OutputFormat.svc>
- <https://example.com/ISHWS/Wcf/API25/PublicationOutput.svc>
- <https://example.com/ISHWS/Wcf/API25/Search.svc>
- <https://example.com/ISHWS/Wcf/API25/Settings.svc>
- <https://example.com/ISHWS/Wcf/API25/TranslationJob.svc>
- <https://example.com/ISHWS/Wcf/API25/TranslationTemplate.svc>
- <https://example.com/ISHWS/Wcf/API25/User.svc>
- <https://example.com/ISHWS/Wcf/API25/UserGroup.svc>
- <https://example.com/ISHWS/Wcf/API25/UserRole.svc>
- <https://example.com/ISHWS/Wcf/API20/Application.svc>
- <https://example.com/ISHWS/Wcf/API20/DocumentObj.svc>
- <https://example.com/ISHWS/Wcf/API20/EDT.svc>
- <https://example.com/ISHWS/Wcf/API20/EventMonitor.svc>
- <https://example.com/ISHWS/Wcf/API20/Folder.svc>
- <https://example.com/ISHWS/Wcf/API20/MetaDataAssist.svc>
- <https://example.com/ISHWS/Wcf/API20/OutputFormat.svc>
- <https://example.com/ISHWS/Wcf/API20/Publication.svc>
- <https://example.com/ISHWS/Wcf/API20/PublicationOutput.svc>
- <https://example.com/ISHWS/Wcf/API20/Reports.svc>
- <https://example.com/ISHWS/Wcf/API20/Search.svc>
- <https://example.com/ISHWS/Wcf/API20/Settings.svc>
- <https://example.com/ISHWS/Wcf/API20/Workflow.svc>
- <https://example.com/ISHWS/Wcf/API/Application.svc>
- <https://example.com/ISHWS/Wcf/API/ConditionManagement.svc>

ISHSTS with Windows Authentication

You need to perform several settings before ISHSTS can provide Windows Authentication. Both server and SQL server database must be properly configured. You can either make these settings manually or use the scripts provided with the package.

ISHSTS is automatically configured through the installation.

InstallTool creates an application pool such as `TrisoftAppPoolISHSTS` based on the input parameter `infosharestswebappname`. The application pool is assigned an identity based on the input parameter `osuser`. This user is responsible for hosting the endpoints provided by ISHSTS

For Windows Authentication endpoints to work, the following changes based on the requirements of `Service Principal Names` defined in the Active Directory must be made, either manually or through a script.

Note: The following needs to be applied per installation server and are valid only for deployments that do not include network balanced front end servers

Application pool identity

A change of the application pool identity in order to use the integrated `ApplicationPoolIdentity`. This changes the user who hosts the endpoints to an account that the correct `Service Principal Names` is assigned to. The expected `Service Principal Names` are

- `http/baseurl`
- `host/baseurl`

Note: The new user is identified locally as `IIS AppPool\infosharestswebappname` and it requires certain permissions to access resources. When this user accesses network resources it is identified as the computer account `Domain\ Computer$` where the `Domain` and `Computer` are netbios based. e.g. `TESTDOMAIN\SERVER01$`

Read permissions

Read permissions to the token signing certificate's private key are assigned to the `IIS AppPool\infosharestswebappname`. The token signing certificate in ISHSTS is configured through the InstallTool parameter `issuercertificatethumbprint`

Read/write permissions to the three target installation paths defined in the input parameters are assigned to the `IIS AppPool\infosharestswebappname`:

- `webpath`
- `datapath`
- `apppath`

Integrated authentication

If the database is SQL Server and the connection string utilizes integrated authentication then we grant the computer account permissions to the database.

The only permission required is `SELECT`

Configure application server for Windows Authentication

Here is how you execute the script that configures the server for ISHSTS with Windows Authentication.

Before you begin

This task requires a PowerShell session that with `Execution Policy` set to `Unrestricted`. If it is not set, you need to set it permanently by executing the following:

```
Set-ExecutionPolicy Unrestricted
```

The task requires administrator privileges.

Note: InstallTool has already transformed the script based on the input parameters.

Procedure

1. Locate the PowerShell script `SDL.ISH-ISHSTS-Configure for Windows Authentication.ps1` in the folder `\InfoShare\App\Setup\STS\ISHSTS\Scripts`
2. Open PowerShell with elevated administrator privileges. `Run As Administrator`. If the PowerShell session is not running with administrator privileges, the script will launch a new session and administrator privileges will be requested to the user.
3. Navigate to the script folder `\InfoShare\App\Setup\STS\ISHSTS\Scripts`
 - a. `cd \InfoShare\App\Setup\STS\ISHSTS\Scripts`
4. Execute script `SDL.ISH-ISHSTS-Configure for Windows Authentication.ps1`
 - a. `.\SDL.ISH-ISHSTS-Configure for Windows Authentication.ps1`

PowerShell session

```
cd \InfoShare\App\Setup\STS\ISHSTS\Scripts  
& '.\SDL.ISH-ISHSTS-Configure for Windows Authentication.ps1'
```

Configuring the Content Manager SQL Server database for Windows Authentication

Here is how you execute the script that allows the server's computer account to access a SQL Server database.

Before you begin

The task applies for SQL Server database when the connection string used integrated authentication.

The task requires sysadmin rights on the SQL Server.

Note: InstallTool has already transformed the script based on the input parameters.

Procedure

1. Locate the script `GrantComputerAccountPermissions.sql` in the `\InfoShare\ App\ Database\ InfoShareCM\ Common\` folder. Depending on your version of SQL Server:
 - For SQL Server 2019, the script path is `\InfoShare\ AppPROJECTSUFFIX\ Database\ InfoShareCM\ Common\ SQLServer2019\ Tools\ GrantComputerAccountPermissions.sql`
 - For SQL Server 2017, the script path is `\InfoShare\ AppPROJECTSUFFIX\ Database\ InfoShareCM\ Common\ SQLServer2017\ Tools\ GrantComputerAccountPermissions.sql`where `PROJECTSUFFIX` is a suffix string.
2. Execute the script on the target SQL server instance.

SQL Server script that grants necessary permissions

If the target database is `INFOSHAREDB` and the computer account is `TESTDOMAIN\SERVER01$` then the script looks like this:

```
USE [master]
GO
CREATE LOGIN [TESTDOMAIN\SERVER01$] FROM WINDOWS WITH DEFAULT_DATABASE=
[INFOSHAREDB]
GO
USE [INFOSHAREDB]
GO
CREATE USER [GLOBAL\MEDEVASARAFIA01$] FOR LOGIN [TESTDOMAIN\SERVER01$]
GO
USE [INFOSHAREDB]
GO
GRANT SELECT TO [TESTDOMAIN\SERVER01$]
GO
```

Verifying the installation

Conduct some testing to verify critical parts of your installed system.

Verifying URLs

If your environment includes reverse proxy servers, after you install Content Manager, you need to check that certain URLs are accessible.

Procedure

1. Using an internet browser, ensure that you can reach the following URLs:
 - *BaseURL*/ISHWS/Application.asmx?wsdl
 - *BaseURL*/ISHWS/Application.asmx?disco where *BaseURL* is the value specified for the `baseurl` parameter, and *ISHWS* is the value specified for the `infosharewebappname` parameter. These parameters are set in the `inputparameter.xml` file that is used by the Content Manager installer.
2. If you cannot access the URLs, verify that the reverse proxy servers are correctly configured. See the documentation for the reverse proxy servers.

Verify read access to the database by viewing an inbox

To verify read access to the database, request to view an inbox in Organize Space.

Procedure

1. Open an internet browser and enter the address for Organize Space.

Note: The Organize Space address is a combination of two parameter values in the parameters in the `inputparameters.xml` file, `baseurl` and `infosharecswebappname`, followed by the string `/OrganizeSpace/`

For example, if:

```
<param name="baseurl">
<currentvalue>https://example.corp</currentvalue>
```

and

```
<param name="infosharecswebappname">
<currentvalue>ISHCS</currentvalue>
```

then the URL is:

```
https://example.corp/ISHCS/OrganizeSpace/
```

Enter a Content Manager username and password. If you are not sure about the login/password and you imported the default database you can use **admin/admin** to login.

2. On the top tab level, select the **Content** tab.
3. On the second tab level, select the **Inbox** tab.
4. In the left pane, select an inbox. For example, select **Reviewer**.
If no objects are in the inbox, an empty inbox is displayed; **There are no items to show** is reported in the content pane.
If there are objects in the inbox, a list of objects is displayed in the content pane.

Verify read and write access to the database by creating a folder

Create, modify, and delete actions are handled through transactions and verifies read and write access to the database.

Procedure

1. Sign in to Organize Space as an existing user, for example as the administrator user.
2. On the top tab level, select the **Content** tab.
3. On the second tab level, select the **Structured Content** tab.
4. Select the **General** node and select **Add new > Folder**.
An Add new folder dialog opens.
5. Enter a name in the **Folder Name** field. For example, enter the folder name **Test**.
6. Under **Content type**, select **None**.
7. Select **OK**.
The folder is created and displayed in the left pane.

What to do next

You can remove the test folder by selecting it in the list and then selecting **Delete** in the button toolbar. You are asked to confirm the delete action, select **Delete** to confirm and delete the folder.

Creating an account and connecting to the Repository

Before you can use Content Importer, you need to set up your user account. If you installed Content Importer on a system where Publication Manager is already installed, the user account settings are recognized.

Before you begin

You must create the user account and configure the connection to the Repository to allow a user to connect and access data in the Content Manager Repository. Use this procedure to create a new user account for testing purposes.

To create the account and connect to the Repository, you need the URL of the Content Manager web services.

Procedure

1. In Content Importer, select **Create an account**.
The account window is displayed.
2. Enter an **Account Name** and the URL of the Content Manager **Web Service**.
3. Select **Next**.
4. If necessary, select the **Authentication Method**.
5. Enter the username and password.
Check **Remember password** if you do not want to enter the information each time you use the application.

6. Select **Next**.

Content Manager validates the account and synchronizes files.

Running a client tool

When started, the client tools verify availability of the synchronization website and web services.

Before you begin

- A desktop client workstation must be installed with the client tools. If not done, refer to the section for installing desktop clients.
- The client tool must be configured with a user login and account.
- To fully test the client, the database should contain data.

Procedure

1. If necessary, create an account and connection to the repository.
2. Start a client tool such as Publication Manager, Condition Manager or Authoring Bridge from the **Start** menu or desktop shortcut.

If you can view and access the repository through the client tool, and can view or preview a topic in the repository then web services, synchronization, and network availability have been successfully verified.

Testing publishing

You can test the publish functionality if your database contains topics, maps and publications, and it is configured to render an output type.

Before you begin

If your database is not configured to render an output, refer to the [Content Manager Information Portal](#) documentation for information about adding output formats.

Procedure

1. Sign in to Organize Space as an existing user, say, the administrator.
2. On the top tab level, select the **Content** tab.
3. On the second tab level, select the **Structured Content** tab.
4. In the folder tree, navigate to a folder that contains a publication you want to publish.
5. In the list, double-click the publication.
A detail view of the publication appears.
6. Expand the version of the publication that you want to publish, and select language and output for the publication version.
7. Select **Publish** in the button toolbar at the top.
A dialog reports that publishing has started, and invites you to see event details.
8. To display progress, select **View event details** or select **Refresh** in the button toolbar above the list.

When viewing event details, verification is complete when the Event Description is **Publish Process ended** and the status says **SUCCESS**.

Executing the full text search

You can test the search functionality if the database contains content.

Procedure

1. Sign in to Organize Space.
2. On the top tab level, select the **Content** tab.
3. On the second tab level, select the **Search** tab.
4. Think of a word that frequently occurs in your content, enter that word in the **Search for** field and press **Enter** (or select **Apply**).

If there is no search result, verify if a rebuild of the full-text-index collection is required. Note that the full-text-index collection is not immediately available after installation since it takes some time to build.

Verifying customer specific components

If you requested customizations of the out-of-the-box Content Manager software, a check that they were delivered is recommended at this time.

About this task

Customizations of the delivered software may be, for example, PDF stylesheets, extra metadata, or extra development to integrate with other systems such as SDL-TMS, PLMs, SingleSignOns.

If you contracted for additional customizations, check that they were delivered and functioning as required.

Advanced topics for installation

These advanced topics deal with the InstallTool and with firewalls and blocked ports.

InstallTool

InstallTool is a command line-driven application which allows you to install Content Manager, including customer-specific files and components.

InstallTool overview

InstallTool logs all installation actions and keeps an installation history which allows you to rollback.

InstallTool was developed to:

- reduce the time needed to install Tridion Docs
- eliminate the most common mistakes when installing Tridion Docs
- provide reproducible installations over DEV, QA and PROD
- provide a framework for system integrators to deploy a customer-specific Content Manager application
- make it easier to have multiple Content Manager applications on one server

Training is available on how to build and maintain the InstallTool package. Note that the Generate InstallPlan option cannot take into account all variations of all possible setups or all possible options. Manual actions on the InstallPlan may be required to describe your installation. InstallTool is only available to generate the initial file.

Executing the program consists of starting InstallTool and following the instructions. The Content Manager Database should be up and all Microsoft components and Third Party Software should be installed.

The InstallTool package

The InstallTool package contains the root of your CD location and two files, `InstallPlan.xml` and `InputParameters.xml`.

The root of your CD location

It is a folder on your file system that uses the Content Manager official structure containing the raw data.

InstallPlan.xml

The InstallPlan is generated by Content Manager or an integrator. It describes the installation. That is, it describes every install action such as the source and target folder for every file, Virtual Directories, Registry structures, Services and so on.

An install plan is built from two types of building blocks:

- file elements (from-to copy statements)
- webapp/registry/serviceapp (system change statements)

These building blocks are in the following three groups:

- Standard (the out-of-the-box components for the project/environment).
- Customer Specific (your customized/project files overwriting the Standard/DITA files).

Note that if you add files to the CD, you must regenerate the install plan, otherwise it does not contain extra file elements.

InputParameters.xml

This file contains a list of variables that require a value assignment from the system administrator. The main goal is to centrally define global settings such as `AppPath`, `WebPath`, `DataPath`, `ProjectName`, `Designated OSUser`, `database ConnectString`, and so on.

The file contains the prompts displayed in a graphical user interface of an install program. All these values are inserted in the necessary places during the installation.

The `InputParameters` file needs to assign a value for ALL variables used somewhere in the `InstallPlan.xml` or in files which use variables on the CD.

Unimplemented features of the InstallTool

InstallTool must know about all Content Manager options, features, and environment changes that are impossible however, some operations are not automated.

For reasons of security and complexity, the following operations are not automated:

- Installing SQL Server or Oracle.
- Running scripts on an existing database.
- Creating the designated operating system user.
- Changing the transaction timeout settings.
- Delta upgrading of environments (only full (un)install).
- Checking the availability of correct Microsoft components.

There are some additional, manual configurations or edits that need to be done included in the procedure for installing or upgrading.

Firewalls and blocked ports

There is a variety of possibilities regarding network and firewall configurations. Only some of typical firewall configurations are described. A user knowledgeable about networking can infer the required ports and protocol settings needed for more complex configurations.

Note: The following description is intended to guide you in your network and firewall configuration. Its intention is not to be a complete how-to guide for setting up firewalls. Several settings are subject to change in newer software versions. Be certain to refer to the latest reference materials.

Network configuration using a single firewall

The first firewall is located between the Internet and the internal network

This is the first line of protection from the world wide web. All information passed through the Content Manager web sites or web services are based on the HTTPS protocol.

The techniques described in the section for HTTPS (SSL) could be required depending on the task of the Content Manager server.

Network configuration using two firewalls

The first firewall is located between the Internet and the DMZ as described above and the second is located between the DMZ and the intranet

The second line of protection protects servers which are open to the general public from the more critical company intranet servers. The zone between the first and second line of protection is also called the DMZ (DeMilitarized Zone).

The following techniques could be required depending on the task of the Content Manager server

- SMTP - when SMTP communication is required
- Database engines
 - Microsoft SQL Server access is required
 - Oracle database access is required
- HTTP(S)

SMTP

Ports and protocols used by the Simple Mail Transfer Protocol (SMTP).

Simple Mail Transfer Protocol (SMTP) is the standard for e-mail transmissions across the internet. Formally SMTP is defined in RFC 821 (STD 10) as amended by RFC 1123 (STD 3) chapter 5. The protocol used today is also known as ESMTP, and it is defined in RFC 2821.

Used by:

- Content Manager Publishing components
- Content Manager Author components

Settings:

What	Protocol	Port	Direction
SMTP	TCP	25	IN/OUT

For more information, refer to:

- <http://msdn2.microsoft.com/en-us/library/ms942998.aspx>
- <http://en.wikipedia.org/wiki/SMTP>

Microsoft SQL Server ports

Ports and protocols used by Microsoft SQL Server database engine (SQLServer).

About this task

Microsoft SQL Server is a relational database management system (RDBMS) produced by Microsoft. Its primary query language is Transact-SQL, an implementation of the ANSI/ISO standard Structured Query Language (SQL) which is used by Microsoft. You need to allow distant users to connect to the SQL server so they can address it their queries.

SQL Server is used by:

- Content Manager End User components;
- Content Manager Author components;
- Content Manager Database.

Note: The first step of this procedure is sufficient in most cases. Go through the other steps if you encounter any issue.

Procedure

1. Enable remote connections to your SQL Server.
 - a. Open **SQL Server Management Studio**.
 - b. Right-click your server's name and select **Properties**.
 - c. Tick the checkbox **Allow remote connections to this server**.
 - d. Select **OK**.

Microsoft SQL Server by default uses TCP 1433 but this can be changed using **SQL Server Enterprise Manager** or the database **Management Studio**.

2. Enable TCP/IP.
 - a. Open the **SQL Server Configuration Manager**.
 - b. In **SQL Server Network Configuration** select **Protocols for [yourServerInstance]**.
 - c. In the right-hand pane, make sure that **TCP/IP** is **Enabled**.
3. Open the 1433 port in your firewall.
 - a. In the **SQL Server Configuration Manager**, right-click **TCP/IP** and select **Properties**.
 - b. Select the **IP Addresses** tab and make sure the **TCP Port** for **IP1** is **1433**.
4. If you are using a named instance, create an extra rule in your firewall with the port 1434.

Note: For a named SQL Server instance (e.g. [yourServerInstance] \ SQL2012SP2), the firewall needs an extra rule on the UDP protocol with the specific port 1434. Without this rule the system will return the exception error: 26 - Error Locating Server/Instance Specified.

- a. Display the firewall advanced settings by navigating to **Control Panel > System and Security > Windows Firewall > Advanced settings**.
- b. Select **Inbound Rules** in the left-hand pane, then click **New Rule** in the right-hand pane.
- c. In the **New Inbound Rule Wizard, Rule Type step**, select **Port**.
- d. **Protocols and Ports** step, select **UDP** and set **Specific local ports** to **1434**.

- e. **Action** step, select **Allow the connection**.
- f. **Profile** step, tick the **Domain** checkbox.
- g. **Name** step, enter a name for this rule, e.g. `Named instance port 1434`.
- h. Select **Finish**.

What to do next

For more information, refer to:

- <http://support.microsoft.com/kb/287932>
- <http://msdn.microsoft.com/en-us/library/ms942998.aspx>

Oracle ports and protocols

Ports and protocols used by Oracle.

Oracle Database or simply Oracle is a relational database management system (RDBMS) software product released by Oracle Corporation that has become a major feature of database computing.

Used by:

- Content Manager End User components
- Content Manager Author components
- Content Manager Database

The Oracle database server communicates with the Content Manager application server using a port, so make sure this port is opened IN/OUT in your firewall. The port by default is 1521.

What	Protocol	Port	Direction
Listener (runs on the database server)	TCP	1521 (default)	IN/OUT

HTTPS (SSL)

Ports and protocols used by Microsoft Internet Information Server (IIS).

HTTPS is a URI scheme used to indicate a secure HTTP connection. It is syntactically identical to the `http://` scheme normally used for accessing resources using HTTP. The `https:` URL indicates that HTTP is to be used but with a different default TCP port (443) and an additional encryption/authentication layer between the HTTP and TCP.

HTTPS is not a separate protocol, but refers to the combination of a normal HTTP interaction over an encrypted Secure Sockets Layer (SSL). An `https:` URL may specify a TCP port. If it does not, the connection uses port 443.

Used by:

- Content Manager End User Website

2 Installing Content Manager

- Content Manager Author Website
- Content Manager WebServices

Settings:

What	Protocol	Port	Direction
HTTPS	TCP	443	IN/OUT

3

Troubleshooting Content Manager installation

Should you run into an installation issue, here are recommendations on how to deal with it.

Contacting customer support

This section contains information about where to go for additional information about the Content Manager product, what to do if you experience a problem with your system, and whom to call for service when necessary.

Diagnosing Problems

There are a number of ways you can help the Content Manager support team resolve your issue solved in an efficient way.

Introduction

- Make sure the defect isn't caused by an external cause: problems might be caused by reasons external to the application, for example, disk space not sufficient, controller error, network down, etc. Software issues can also be caused by incompatibilities among programs.
- Make sure the problem isn't caused by data issues: verify that the problem occurs for all sets of data, not just one specific data set.

Use Windows Event Viewer to discover External Failures

You can use the **Event Viewer** in Windows. **Event Viewer** maintains logs about program, security, and system events on your computer. You can use **Event Viewer** to view and manage the event logs, gather information about hardware and software problems, and monitor Windows security events.

To open **Event Viewer**, click **Start > Settings > Control Panel > Administrative Tools > Event Viewer**.

Providing Information

When entering issues, please describe the steps needed to reproduce the problem and provide other pertinent information.

When contacting support for Content Manager, please provide information about:

- The user interface in which the problem occurs
- The frequency with which the problem occurs
- The menus or dialog boxes you are using
- The specific elements or attributes that are causing problems
- Any error messages you are receiving
- Any screenshot that may help the support representative understand the problem

- A copy of the log file generated by your authoring tool, if you feel it is pertinent
- The GUID of the repository object that is causing problems,
- Whether the problem is preventing you from releasing crucial documentation
- Any other information which can help our support team replicate your problem

Log Files

Information in the log files is valuable to you and the Content Manager support team when investigating and troubleshooting issues.

Using log files

To use a log file most effectively, it is important that the log file only contains the information or steps necessary to reproduce the problem.

About this task

Tip: If the system is used quite intensively by multiple users, try to do this during a time when activity is low (for instance, lunch or in the evening).

Procedure

1. Navigate to the folder that contains the log file.
2. Rename the most recent log file.
3. Repeat the steps needed to reproduce the problem. Since all actions from all users are logged in the same log file, this needs to be done as quickly as possible.
A new log file is generated which contains logging for steps needed to reproduce the problem.
4. Move the file to a subfolder or rename it by adding a bug tracker number or a short description of what you reproduced.

Server Logs

Content Manager relies on third-party software products such as Microsoft Windows Server, Microsoft SQL Server, Oracle, Java Runtime Environment, DITA-OpenToolkit, AntennaHouse XSLFormatter, and so on, which generate log files that are stored on the server.

Microsoft Windows logs

Applications and operating system components often make use of the **Event Viewer**. Event viewer is centralized log service to report events that have taken place such as a failure to start a component or complete an action.

To open Event Viewer: **Settings > Control Panel > Administrative Tools > Event Viewer**

Note: Although Content Manager has its own logging mechanism, it uses Event Viewer when there is limited or no free database space.

Content Manager .NET component logging

The following .NET components are driven through the NLog logging library and are configured with the `NLog.config` file located next to the hosting process.

Application	Is NLog enabled	Typical Configuration Path relative to <code>C:\InfoShare\</code>	Initial Log File Path relative to <code>C:\InfoShare\</code>	Typical Log File Path relative to <code>C:\InfoShare\</code>
Crawler.exe	Yes	App\Crawler\Bin\NLog.config	N/A	Data\Logs\InfoShareBuilders_pid2944_20130607.log
TrisoftSolrLucene	Yes	App\TrisoftSolrLucene\Bin\NLog.config	N/A	Data\Logs\TrisoftSolrLucene_pid7884.log
BackgroundTask	Yes	App\BackgroundTask\Bin\NLog.config and App\BackgroundTask\Bin\NLog.Iso.config	N/A	Data\Logs\BackgroundTask_pid14164_20190109.log Contains entries from the BackgroundTask service components, including entries from the executing handlers components. Data\Logs\BackgroundTaskIso_pid1234_20190109.log Contains entries for the isolated background tasks for any handlers having <code>isolationLevel="Process"</code> in their XML configuration.
Trisoft.InfoShare.Web	Yes	Web\Author\Asp\NLog.config	N/A	Data\Logs\Trisoft.InfoShare.Web_2013_06_17.log
ISHWS	Yes	Web\InfoShareWS\NLog.config	N/A	Data\Logs\InfoShareWS_20130617.log
PublishResult	Yes	App\Utilities\PublishResult\NLog.config	N/A	Data\Logs\PublishResult_pid2944_20130607.log
ISHSTS	Yes	Web\InfoShareSTS\NLog.config	N/A	Data\Logs\InfoShareSTS_20130617.log
TranslationBuilder	Yes	App\TranslationBuilder\Bin\NLog.config	N/A	Data\Logs\TranslationBuilder_pid7276_20130617.log

Application	Is NLog	Typical Configuration Path relative to C:\InfoShare\	Initial	Typical Log File Path relative to C:\InfoShare\
Translation Organizer	Yes	App\TranslationOrganizer\Bin\NLog.config	N/A	Data\Logs\TranslationOrganizer_pid5416_20130617.log
SynchronizeToLiveContent	Yes	App\Utilities\SynchronizeToLiveContent\NLog.config	N/A	Data\Logs\SynchronizeToLiveContent_20130617.log
PublishService	Yes	App\Utilities\PublishingService\Tools\NLog.config	N/A	Data\Logs\FeedSDLLiveContent_20130617.log
ISHCM	Yes	AppCore\Common\Configuration\NLog.config	No	DataCore\Logs\InfoshareAuthorApp_20130607.log
			Yes	Data\Logs\InfoshareAuthorApp_20130607.log
FontoXml.Apps.Review.exe	Yes	App\Utilities\FontoReview\NLog.config	N/A	Data\Logs\FontoReview_pid4248_20191219.log
FontoXml.Apps.DocumentHistory.exe	Yes	App\Utilities\FontoDocumentHistory\NLog.config	N/A	Data\Logs\FontoDocumentHistory_pid2868_20200116.log
Fonto.Content.App.exe	Yes	App\Utilities\FontoContentQuality\NLog.config	N/A	Data\Logs\FontoContentQuality_pid14728_20211115.log
InstallTool.exe	No	DefaultInstallToolLog in InstallTool.exe.config	N/A	.\InstallTool.log
DBUpgradeTool.exe	No	DefaultDBUpgradeToolLog in App\Setup\DBUpgradeTool\DBUpgradeTool.exe.config	N/A	.\DBUpgradeTool.log

Note: Modifications to the NLog configuration are immediately applied without the need to restart the hosting process.

Content Manager Java component logging

The following Java components are driven through the Jetty logging library and are configured with the `jetty-logging.xml` file.

Application	Parent process	Is NLog	Typical Configuration Path relative to C:\InfoShare\	Initial	Typical Log File Path relative to C:\InfoShare\
java.exe (OpenJDK Platform binary)	Trisoft-SolrLucene	No	App\Utilities\SolrLucene\Jetty\etc\jetty-logging.xml	N/A	Data\Logs\JettySolrLucene.stderrout_2020_02_10.log

Note: Modifications to the jetty-logging.xml configuration are not immediately applied and need to restart the hosting process.

Desktop client logs

Logs are produced for the Publication Manager, Condition Manager, Authoring Bridge, and Launcher and are stored in a log directory on the local client system.

Log file location

The log files are all located in the following folder on the client system:

`C:\Users\USER_NAME\AppData\Local\RWS\InfoShare Client\VERSION\Log\`

Available log files

The following table summarizes the log files for the various desktop client tools:

Client Tool	Log file name
Authoring Bridge	Oxygen Connector.log
	XMetaL Connector.log
Condition Manager	Condition Manager.log
Content Importer	Content Importer.log
Content Importer conversion	Content Importer - Import Report.log
Launcher	InfoShare Launcher.log
Publication Manager	Publication Manager.log

Synchronized application configuration

The synchronized application configuration (DTDs, Preview, Metadata,...) files are located in the following user directory: `C:\Users\USER_NAME\AppData\Local\RWS\InfoShare Client\VERSION\Config`

For example: `C:\Users\kcat\AppData\Local\SDL\InfoShare Client\0015454899\Config`

User data

The user data, such as temporary stored images or checked out objects, are stored in the user directory: `C:\Users\USER_NAME\My Documents\RWS\InfoShare\NUMBER\Admin`

For example: `C:\Users\kcat\My Documents\SDL\InfoShare\0015454899\Admin`

Note: In the examples above, *NUMBER* is 0015454899 which is a hashed version of the repository location, web services virtual directory name, and the application name. This was done to avoid file path issues since a Windows file path is limited to 260 characters. There is an informational folder created inside the cryptic number folder which indicates to which repository the stored information is related, for example: `example.com_ISHWS_ISHCM`

Configuring logging for Content Manager .NET components

Content Manager .NET components are driven through the NLog logging library. You can increase or decrease the logging by modifying the `NLog.config`.

About this task

The following table describes the different log levels:

Log level	Description
Trace	For tracing the program flow and performing the finest level of debugging—logs messages with the highest level of detail about the application's lowest-level activity.
Debug	For normal debugging—logs fine-grained messages about low-level functionality being executed, intended to discover the source of a problem.
Info	Logs information messages related to normal activity and user behavior, plus all warnings and errors.
Warn	Logs warnings of unexpected events as well as all errors.
Error	Logs all errors—both fatal events and non-fatal errors.
Fatal	Logs only critical errors, that is, events that cause the system to go down.

By default, only `Fatal`, `Error`, and `Warning` messages are logged.

Note: For more information about configuring logging, refer to the [NLog Configuration file](#).

Procedure

1. Open `NLog.config` file for editing.
The logging configuration file `NLog.config` is, by default, located in the application's directory, for example: `C:\Program Files\RWS\Publication Manager\15.0`.
2. Change the logging level, as needed.

To enable maximum logging, set the minimum level to `Trace`.

```
...
    <logger name="*" minLevel="Trace" writeTo="File"/>
...
```

3. Save and close the file.

Sample configuration file

The following configuration indicates that all messages, from any class in the application whose level is `Warn` or higher, that is, `Warn`, `Error`, and `Fatal`, are written to the file `Publication Manager.log`.

```
<nlog xmlns="http://www.nlog-project.org/schemas/NLog.xsd"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <include file="NLog.Include.ClientApplications.config"/>
  <targets>
    <target name="File"
      xsi:type="File"
      layout="${fileLayout}"
      fileName="${specialfolder:folder=LocalApplicationData}\SDL\InfoShare
Client\12.0\Log\Publication Manager.log"
      archiveAboveSize="2000000"
      maxArchiveFiles="3"
      archiveNumbering="Rolling"
      keepFileOpen="false"
    />
  </targets>
  <rules>
    <logger name="*" minLevel="Warn" writeTo="File"/>
  </rules>
</nlog>
```

Event Log content

The **Event Log** contains detailed information about all background processes. For example, it contains information about each step of the output generation, and contains warning and error information that can help you troubleshoot output generation failures.

Administrator users have access to event logs for warnings, failures, are in progress, or recently occurred. The event logs include information about:

- Translation Management
- Translation Jobs
- Lower-level Element Reuse
- Export
- Publish
- Synchronize with the delivery platform
- Thumbnails
- All Events

Information in the log files is valuable to your support team when investigating and troubleshooting issues. Copy the information and forward it with your issue report to your customer support representative when requesting assistance or reporting an issue.

Using the Event Log

Information in the event log helps you and RWS customer support to troubleshoot problems you may encounter.

Before you begin

To perform this task, a user must have System Administrator privileges.

Procedure

1. Sign in to Organize Space as a user with administrator-level credentials.
2. Select the **Events** tab.
3. On the left, select the type of event or log file for which you want to see logs.
4. At the top of the content area, select an option to see a selection of logs:
 - **Show Recent** shows logs from the last 24 hours.
 - **Show Failed** shows logs that resulted in a failed status.
 - **Show Busy** shows logs for events that are currently running.
 - **Show Warning** shows logs for events that ended successfully, but with one or more warnings.
 - **Show All** shows all saved logs for this type of event.
5. To further filter the list of logs displayed, type text in the search box at top right. As you type, the list narrows to only those logs that contain the text you type in any of its fields.
6. From the list of logs, select the log of the event you want to see.
The bottom part of the content area shows individual log entries for the log you selected.
7. To see a highly detailed list of log entries, select **Show Verbose**. Select **Hide Verbose** to return to the original list of log entries.
8. To further filter the list of log entries displayed, type text in the search box on the right. As you type, the list narrows to only those log entries that contain the text you type in any of its fields.
9. To see even more details for an individual log entry, select that log entry.
An **Event Details** popup dialog opens showing all details for that log entry. When you are done examining it, select **Close** to close it.

Troubleshooting the database installation

When the database returns errors after creation or import, check the available corrective actions.

What to do if Oracle database import fails

If the import fails, you may want to remove the designated ISOURCE database user and all the objects it owns before you can try again.

Procedure

1. Start SQLPLUS /NOLOG from a shell where the ORACLE_SID and ORACLE_HOME variables are set correctly; at a command prompt type:

```
CONNECT SYS/CHANGE_ON_INSTALL AS SYSDBA
DROP USER ISOURCE CASCADE;
```

2. Recreate the ISOURCE user.

What to do in case of "ORA-12638" error

A freshly installed Oracle database sometimes results in ORA-12638 errors. If you are running a dedicated Content Manager Oracle server, you can resolve problems by altering the SQLNET.AUTHENTICATION_SERVICES setting.

Note: If you are not running a dedicated Content Manager Oracle server, contact your Oracle DBA.

1. Open Oracle file `\network\admin\sqlnet.ora`
2. Change the value of parameter **SQLNET.AUTHENTICATION_SERVICES** to **(none)**. This setting is instead of (NTS).

User is restricted or does not have permissions

Login errors can occur if a user restriction is set or the user does not have proper permissions.

Login time restriction

Login fails because there is a logon time restriction.

Problem

The user sees the following error:

```
Logon failure: account logon time restriction violation
```

Explanation

The **Logon hours** restriction is selected.

Resolution

Remove the **Logon hours** restriction.

User account restriction

Login fails with a user account restriction error.

Problem

The user sees the following error:

```
Logon failure: user account restriction
```

Explanation

The password has expired, or one of the following is selected:

- **Logon hours** restriction
- **Logon to** restriction
- **Account disabled**

Resolution

To resolve, depending on the cause (see explanation above):

- Change the password. Refer to information about the password or user name locations.
- Remove the **Logon hours** restriction.
- Remove the **Logon to** restriction.
- Re-enable the account.

User not granted requested logon type

Login fails because the user does not have requested login type.

Problem

The user sees the following error:

```
Logon failure: the user has not been granted the requested logon type at this computer
```

Explanation

The account has no **log on as service** permissions, or no **log on as batch job** on the computer.

Resolution

Provide the permissions.

The designated user is running the wrong (date) settings

The designated account is used to set some environment variables or settings. Most common is the Regional Options short date setting. A Windows operating system has two levels of environment variables: the system level and the user level. Know that user settings can override system settings.

System and user settings

An example of environment variables that may be set for both the system and user is the TEMP variable. TEMP may be set to `c:\TEMP\system` for the system, however, when the user SophieC logs in, it may be set to `c:\TEMP\SophieC`.

Other user specific settings such as the Regional Options, are stored in the registry. When a computer starts, the system defaults are loaded. The user level is only loaded upon request, for example, a login to a command prompt login.

The following contains information about user settings that may be helpful:

- The Microsoft knowledge base article **KB257757** describes server-side automation of Office
- The Microsoft knowledge base article **KB288367** describes how to run COM components under a specific user account.

Note: To access Microsoft knowledge base articles, go to the Microsoft support website at <https://support.microsoft.com/> and search for the article number(s).

Resolving certificate problems

Content Manager does not use certificates on a regular basis. It does however, test secure connections for regular web sites and web services.

Content Manager has an internal Certificate Authority (ADS01). It uses the certificates of this server to publish web sites to the world wide web. You must confirm that ADS01 is a trusted authority to use the certificate.

Accepting a certificate using a web browser

When browsing within one session of your browser, it is sufficient to accept the certificate provided from our internal certificate server (normally ADS01).

Problem

The user may see the following **Security Alert**:

Information you exchange with this site cannot be viewed or changed by others. However, there is a problem with the site's security certificate. The security certification was issued by a company you have not chosen to trust. View the certificate to determine whether you want to trust the certifying authority.
Do you want to proceed?

Explanation

As noted, the security certification was issued by a company you have not chosen to trust.

Resolution Click **Yes** to continue with secure communication enabled.

Importing and accepting a certificate for a user

If a user imports the certificate, the user can trust the certificate and be able to connect to the publishing services.

Procedure

1. Double-click on the certificate file.
A Certificate Information window displays.
2. Click **Install Certificate**.
A Certificate Store window displays.
3. Select **Place all certificates in the following store**.
4. Confirm or if necessary, select by clicking the **Browse** button, the Certificate store: **Trusted Root Certificate Authorities**
5. Click **Next**.
A Security Warning window displays.
6. Click **Yes** to install the certificate.

Importing and accepting a certificate for a computer

If a certificate is imported for a computer system, the system can trust the certificate and be able to connect to the publishing services.

Procedure

1. Start the Microsoft Management Console by entering **mmc.exe** at a command prompt.
A Console Root window is displayed.
2. Click **File > Add/Remove Snap-in**
The Add/Remove Snap-in window displays with the Standalone tab selected.
3. Click **Add**.
An Add Standalone Snap-in window displays.
4. Select **Certificates** from the list of available standalone snap-ins, then click **Add**.
A Certificate snap-in window displays.
5. Select **Computer account** to be able to manage all computer account certificates.
6. Click **Next**.
7. Accept the default **Local Computer** and click **Finish**.
8. Click **Close** then **OK** to close the Add/Remove Snap-in window.
The Console Root window is again visible.
9. Under **Certificates (Local computer)**, right-click **Trusted Root Certification Authorities**
10. Click **All Tasks > Import**.
The Certificate Import Wizard window displays.
11. Click **Next**.
12. **Browse** to, and select the certificate (file) to install.
13. Click **Next**.
A Certificate Store window displays.

14. Select **Place all certificates in the following store**.
15. Confirm or if necessary, select by clicking the **Browse** button, the Certificate store: **Trusted Root Certificate Authorities**
16. Click **Next**.
17. Click **Yes** to install the certificate.

Troubleshooting the install tool

Error when running the install tool: RegAsm.exe - .NET Framework Initialization Error

If the Microsoft Server .Net 4.0 is not installed you get errors from InstallTool such as:

```
RegAsm.exe - .NET Framework Initialization Error
```

The NETFramework2010_4.0.30319_(dotNetF40_Full_x86_x64).exe tested with this version of Content Manager can be retrieved online from RWS upon request.

Troubleshooting the crawler service

If the crawler service does not run after the installation, you can unregister and register the crawler service to fix this issue. It should be done using `Invoke-ISHFullTextIndexMaintenance` cmdlet available over `ISHDeploy` module.

Before you begin

- You need to run `ISHDeploy` cmdlets as an administrator for the application server
- To learn how to access and use `ISHDeploy`, refer to the section on “Configuring Content Manager with `ISHDeploy`” on page 0.

Procedure

1. Login into the server as an Administrator user.
2. In a Powershell command shell, enter the following command:

```
Invoke-ISHFullTextIndexMaintenance -ISHDeployment $deployment  
ISHDEPLOYMENT -UnRegister
```

to unregister all crawlers, where `ISHDEPLOYMENT` is the deployment you want to use. (If you have only one deployment, you can omit the `-ISHDeployment` parameter and its value.)

3. In a Powershell command shell, enter the following command:

```
Invoke-ISHFullTextIndexMaintenance -ISHDeployment $deployment  
ISHDEPLOYMENT -Register
```

to register crawler, where `ISHDEPLOYMENT` is the deployment you want to use. (If you have only one deployment, you can omit the `-ISHDeployment` parameter and its value.)

4. If running registering Crawler results in an error message saying, `System.Transactions.TransactionAbortedException: The transaction has aborted. ---> System.TimeoutException: Transaction Timeout`, you can fix this problem by increasing the maximum timeout in the machine settings of the application server. To increase this timeout, do the following:

- a. `Goto%WINDIR%\Microsoft.NET\Framework\v4.0.30319\Config\.`
- b. Open `machine.config` for editing.
- c. Ensure that the `<configuration>` section contains a `<system.transactions>` subsection, which in turn contains a `machineSettings` subelement with a `maxTimeout` attribute. Ensure that that attribute has the value `01:00:00`. The resulting `<system.transactions>` should look as follows:

```
<system.transactions>
  <machineSettings maxTimeout="01:00:00" />
</system.transactions>
```

- d. Save and close `machine.config`.
- e. Run again.

```
Invoke-ISHFullTextIndexMaintenance -ISHDeployment $deployment
ISHDEPLOYMENT -Register
```

Note: By changing the timeout value, you are increasing the timeout period for all .NET applications running on the same machine.
